



## Work lamps

To provide lighting for workstations, drafting machines, laboratories, desks  
Optimal light distribution, pleasant, uniform and without reflections

**Type with 220° swivelling aluminium spotlight, with 3 LEDs, 7W, external Ø 90 mm**

Tempered Pirex glass to protect the LEDs

Lighting characteristics: **14000 lux at 0,3 m - 6000 lux at 0,5 m - 3000 lux at 0,7 m**

Painted aluminium base Ø 60 mm, height 30 mm, with 3 holes for fastening to the workbench using screws

**Protection level IP66 for the optical compartment and IP40 for the component compartment**

**Version for application on workstations**

**Jointed arm, length 200 mm, swivelling**

The spherical base makes it possible to move the lamp in all directions

24V power supply, with 1,8 m long cable

Code N 9092 2000	<b>N 9092/2</b>	Each €		1
------------------	-----------------	--------	--	---



**Version for application on workstations**

**With spiral flexible arm, length 450 mm, coated in plastic and**

swivelling in any direction

Power supply 220 V with adapter, possibility of direct connection to 24 V

Complete with 1,8 m long cable with 10A 2-pole plug

Code N 9092 3000	<b>N 9092/3</b>	Each €		1
------------------	-----------------	--------	--	---

**IP  
66**

Optical  
compartment

**IP  
40**

Components  
compartment

**With 3-jointed arm swivelling to 70° - 132° - 87°**

**Max extension 955 mm**

Power supply 220 V with adapter, possibility of direct connection to 24 V

Complete with 1,8 m long cable with 10A 2-pole plug

Code N 9092 6000	<b>N 9092/6</b>	Each €		1
------------------	-----------------	--------	--	---



**Type with pantograph arm**

**Overall extension 1080 mm**

The pantograph arm with spring balancing allows to effortlessly

position the lamp in any direction.

The perfect calibration of the springs ensures the precision of the movement

**Power 60W**

Frame in drawn steel, electrowelded square tube 10x10 mm

Ceramic lamp holder

Reflector Ø 160 mm with upper structure in fiberglass reinforced nylon and

lower structure in turned iron with finishing edge

Protection level IP20

Can be used with incandescent or LED lamp

1,7 m cable with 2-pole 10A plug

With wing nut for fixing to the bench

Code N 9094 0000	<b>N 9094</b>	Each €		1
------------------	---------------	--------	--	---



Protective shield for lamp N 9094

In tempered glass with grid in galvanised iron

Code N 9094 1000	<b>N 9094/1</b>	Each €		1
------------------	-----------------	--------	--	---



**Type with LED light fixed around the magnifying glass**

**Overall extension 900 mm, with 360° rotation**

Protective screen Ø 127 mm

3 diopters

With integrated transformer

Power supply by mains cable, cable length 1,75 m

With Schuko plug

Protection level IP20

With screw support H 5387/7, opening 55 mm, for bench fixing

Code H 5387 3000	<b>H 5387/3</b>	Each €		1
------------------	-----------------	--------	--	---

