

Suitable for providing a bright and powerful light beam to a specific area or in a specific angle

For universal use on workstations, workshops, laboratories, etc.

Mod. STAR LITE
9 LED SMD LG

300 lumen - 400 lux at 0,5 m

Protection level IP 40

Ergonomic handle with non-slip rubber

Swivel hook for hanging

Power supply 220-230V with **5 m cable** and Schuko plug

Dimensions 26x40x340 mm - Weight 600 g

Code N 9097 3500	N 9097/35	Each €	 1
------------------	-----------	--------	---



IP
40

Mod. SUPERFORM

Slim and handy, suitable for multiple purposes

With 8W high-luminosity COB LED

750 lumen - 1000 lux at 0,5 m

Protection level IP 54 (against dust and water spray)

With 2 swivelling hooks and 2 magnets

Power supply 110-240 V with 5 m cable and Schuko plug

Dimensions 31x49x290 mm - Weight 680 g

Code N 9097 3700	N 9097/37	Each €	 1
------------------	-----------	--------	---

IP
54

IK
08



Tubular profile Ø 25 mm with shockproof acrylic profile


End-covers in shockproof hard rubber

Ergonomic and comfortable design

Light is concentrated in a 75° beam angle: it provides almost double illumination compared to traditional 36W fluorescent tubes

With SPOT light for direct illumination of small parts

The technical lifetime of LEDs is approx. 100000 hours


Mod. LINE LIGHT C

Main light: 36 PLCC SMD LEDs/ 180 lumen

SPOT light: 1 x 1 W LED / 120 lumen

Power supply 220-230V - 50 Hz

Protection level IP 54 (against dust penetration and water splashes)

Supplied with turnable hook and flexible arm with suction cup N 9097/67

Code N 9097 4000	N 9097/4	Each €	 1
------------------	----------	--------	---



IP
54

Mod. LINE LIGHT R

Main light: 16 SMD LEDs

400 lumen - 900 lux at 0,5 m - Operating time approx. 1,5h

SPOT light: 1 CREE XP-G2

150 lumen - 1500 lux at 0,5 m - Operating time approx. 4 h

With magnetic switch to turn the light on or off

Rechargeable Li-ion battery, 3,7 V (2600 mAh)

Charging time about 6 h

IP 65 protection level (protected against dust and water spray)

With swivelling hook and built-in magnet

Provided with charger with USB port N 9097/85 and USB cable

Dimensions Ø 25x357 mm - Weight 220 g

Code N 9097 4500	N 9097/45	Each €	 1
------------------	-----------	--------	---



Magnetic
switch



IP
65

Rechargeable
battery

Mod. LINE LIGHT C + R

Lamp with power cable connection and rechargeable battery

Main light: 24 SMD LEDs

600 lumen - 1300 lux at 0,5 m - Operating time approx. 2,5h

SPOT light: 1 CREE XP-G2

150 lumen - 1500 lux @0,5 m - Approx. operating time 6h

3,7 V (5200 mAh) rechargeable Lithium-ion (Li-ion) battery

Approx. charging time 4h

Protection level IP 54 (against dust penetration and water splashes)

Supplied with charger and turnable hook

Dimensions Ø 25x461 mm - Weight 300 g

Code N 9097 5500	N 9097/55	Each €	 1
------------------	-----------	--------	---



DUAL 2 in 1
SYSTEM



IP
65

Rechargeable
battery