In special forged, oil-hardened steel - DIN ISO 5743

Cutting edges further tempered, approx. hardness HRc 59

«Hamburg» shape with small head, 20 mm, and notch for removing horseshoes

Black atramentized handles - Polished head - 0

Overall length 300 mm - Approx. weight 0,8 kg

B 1903/1 Code B 1903 1000





# Potters' pincer

In special forged, oil-hardened steel - DIN ISO 5743

Cutting edges further tempered, approx. hardness HRc 59

With end cutters for low-resistance wire - Black atramentized handles - Polished head - 0

Head width 20 mm - Overall length 225 mm - Approx. weight 0,4 kg

Code B 1904 0000

**B** 1904

Each €

Each €



## Concreters' nippers

In special hardened, forged, oil-hardened steel - DIN ISO 9242

Cutting edges further tempered, approx. hardness 61 HRc

Suitable for twisting and cutting in a single operation, allowing an easy extraction of nails, wires,

- Jaws with precision cutting edges for a long duration and for effortless cutting operations

#### «Standard» version

**B 1905/0** - Black atramentized handles - Polished head - 0

B 1905/1 - Thermoplastic coated handles - Polished head - 1

B 1905/2 - Entirely nickel-plated

| B 1909/2 - Littillely Hickel-plated |      |             |             |             |             |             |  |  |
|-------------------------------------|------|-------------|-------------|-------------|-------------|-------------|--|--|
| Overall length                      | mm   | 200         | 220         | 250         | 280         | 300         |  |  |
| Code                                |      | B 1905 0200 | B 1905 0220 | B 1905 0250 | B 1905 0280 | B 1905 0300 |  |  |
| <b>B 1905/0</b> Ea                  | ch € |             |             |             |             |             |  |  |
| Code                                |      | B 1905 1200 | B 1905 1220 | B 1905 1250 |             | -           |  |  |
| <b>B 1905/1</b> Ea                  | ch € |             |             |             |             |             |  |  |
| Code                                |      | _           | B 1905 2220 | B 1905 2250 | B 1905 2280 | _           |  |  |
| <b>B 1905/2</b> Ea                  | ch € |             |             |             |             |             |  |  |
| Cuts medium resistence wire Ø       | mm   | 1.8         | 2,4         | 2,4         | 2,8         | 3,1         |  |  |
| Cuts high resistence wire Ø         | mm   | 1,4         | 1,6         | 1,6         | 1,8         | 1,8         |  |  |
| <b>3</b>                            | pcs. | 6           | 6           | 6           | 6           | 6           |  |  |



## Reinforced and tapered version, with high cutting force, compared to traditional nippers, through pin in advanced position

The special shape absorbs cutting vibrations and relieves hand joints

Highest tendons and muscles protection thanks to the absorption of the cutting impact after cutting the wire

B 1906/0 - Black atramentized handles - Polished head - 0

**B 1906/1** - Thermoplastic coated handles - Polished head - 1

| B 1906/2 - Entirely nickel-plated |           |             |             |  |  |  |  |
|-----------------------------------|-----------|-------------|-------------|--|--|--|--|
| Overall length mm                 |           | 250         | 300         |  |  |  |  |
| Code                              |           | B 1906 0250 | B 1906 0300 |  |  |  |  |
| B 1906/0                          | Each €    |             |             |  |  |  |  |
| Code                              |           | B 1906 1250 | B 1906 1300 |  |  |  |  |
| B 1906/1                          | Each €    |             |             |  |  |  |  |
| Code                              |           | B 1906 2250 | B 1906 2300 |  |  |  |  |
| B 1906/2                          | Each €    |             |             |  |  |  |  |
| Cuts medium resistence            | wire Ø mm | 3,3         | 3,8         |  |  |  |  |
| Cuts high resistence wir          | re Ø mm   | 1,8         | 2,0         |  |  |  |  |
| Head length                       | mm        | 25          | 25          |  |  |  |  |
| 1 _                               |           | 6           | 6           |  |  |  |  |



Reinforced version with pin in advanced position compared to traditional nippers



## FABC>TOOLS

Induction-tempered cutting edges - Black phosphated handles - Polished head

| Overall length mm |        | 200         | 220         | 250         | 280         |
|-------------------|--------|-------------|-------------|-------------|-------------|
| Code              |        | B 1907 0200 | B 1907 0220 | B 1907 0250 | B 1907 0280 |
| B 1907            | Each € |             |             |             |             |
| <b>3</b>          | pcs.   | 10          | 10          | 10          | 10          |

