

Self-adjusting stripping pliers

Body in synthetic resin reinforced with fibre glass, special tempered steel blades
Automatic spring opening $\overline{\text{M}}$

For stripping **and cutting, without damaging, single pole copper conductors with multiple wires, with synthetic resin or rubber coated thin wires** without any damage

Gun type

For conductors with section **0,2÷6,0 mm²** (AWG 24-10)

ABC TOOLS

Wire-stripping device with stop, adjustable from 5÷12 mm

Tempered knives for cutting conductors max \varnothing 2 mm

With closing clasp

Overall length 180 mm - Weight 130 g

Code B 2187 2000	B 2187/2	Each €		1
------------------	----------	--------	---	---

KNIPEX

Wire stripping device with adjustable stop 6÷18 mm

With cutter for cutting conductors up to 2,5 mm²

Soft rubber handles

Overall length 180 mm - Weight 180 g

Code B 2187 3000	B 2187/3	Each €		1
------------------	----------	--------	---	---

Wire-stripping device with stop, adjustable from 2÷20 mm

The blade pressure can be adjusted through the wheel placed on the head

Cutter for cutting conductors up to 6,0 mm²

Overall length 170 mm - Weight 200 g

B 2187/5 - 

B 2187/6 - **ABC TOOLS**

Code B 2187 5000	B 2187/5	Each €		1
------------------	----------	--------	---	---

Code B 2187 6000	B 2187/6	Each €		1
------------------	----------	--------	---	---

For multiple-wire conductors **0,5-16 mm²** (AWG 20-6) and single pole conductors **0,5-10 mm²** (AWG 20-8)

ABC TOOLS

Strips 2-wire flat cables with PVC insulation sheath 0,75-1,5 mm²

Tempered blade for cutting conductors up to \varnothing max 3 mm

Overall length 170 mm - Weight 220 g

Code B 2187 8000	B 2187/8	Each €		6
------------------	----------	--------	---	---

For conductors used in photovoltaic systems with section from **1,5÷6 mm²** (AWG 15-9) and also for normal conductors

ABC TOOLS

Wire-stripping device with stop, adjustable from 8÷24 mm ($\frac{5}{16}$ "÷1")

With cutter for cutting conductors max \varnothing 3 mm (not suitable for solar photovoltaic systems)

Overall length 180 mm

Code B 2188 1000	B 2188/1	Each €		1
------------------	----------	--------	---	---

KNIPEX

Straight type with cutter for cutting multiple wire copper and aluminium conductors up to 10 mm² and unipolar wire conductors up to 6 mm

For conductors from **0,03÷16 mm²** (AWG 32-5)

Wire-stripping device with adjustable stop 3÷18 mm

Adjustable cutting pressure for hard synthetic resin coatings

Blocking jaws in synthetic resin

Overall length 200 mm - Weight 200 g

For conductors	mm ²	0,03÷10 (AWG 32-7)*	2,5÷16 (AWG 13-5)
Code		B 2188 3010	B 2188 3016
B 2188/3	Each €		

Spare knives for B 2188/3

For size	0,03÷10	2,5÷16
Code	B 2188 4010	B 2188 4016
B 2188/4	Each €	

For conductors with section up to **0,03÷10 mm²** (AWG 32-7)

Automatic cutting depth regulation

Knurled metal blocking jaws

Handles with inserts in soft anti-slip rubber

For coatings in hard synthetic resin, Teflon® and Radox®

Overall length 195 mm - Weight 140 g

Code B 2188 5000	B 2188/5	Each €		1
------------------	----------	--------	---	---



For conductors used in photovoltaic systems

