Wire stripper, crimping pliers an	nd cable connections				
	- Painted finish nals and stripping cables 0 ded screws M 2.6÷M 5 and				
With synthetic resin handle	9S				
For non-insulated brass	open end sleeves (ferru	lles) 1,5 - 2,5 mm²			
Code B 2193 2000	B 2193/2	Each €	🕞 1		
	sleeves (ferrules) in tinned	(ferrules) 1,5 - 2,5 - 6 mm copper (closed),	²		NORMAN OF
Code B 2193 2100	B 2193/21	Each €	😒 1		
1,5 - 2,5 mm ²	s) 0,5 - 1 - 1,5 - 2,5 - 4 - 6 r caps - Particularly suitable f B 2193/34	mm² and non-insulated o or auto electricians Each €	pen terminals		
Two-component material h For plug end sleeves (fe With hole for spark plug ca Overall length 230 mm	rrules) 0,5 - 2,5 mm² aps				
Code B 2193 2300	B 2193/23	Each €	S 1	l	
For male and female en With hole for spark plug ca Overall length 230 mm	d sleeves (ferrules) 0,5 - aps	6,0 mm²			
Code B 2193 2700	B 2193/27	Each €	S 1		
For end sleeves (ferrule: With hole for spark plugs o Overall length 230 mm	caps				
Code B 2193 3100	B 2193/31	Each €	S 6		
For terminals and conne and non-insulated pin te Overall length 240 mm		es 0,5 - 6 mm²	en e		KRIATE AGEN
Code B 2193 3200	B 2193/32	Each €	S 6		
Crimp gr In high-resistance speci Suitable for pre-insulated to With guick-release lever	ial steel - Burnished finish	20-10) and for stripping cab	oles 0,5÷6 mm²		
Adjustable crimping press Strong crimping with minin Overall length 215 mm		000	9 09		
Code B 2193 4000	B 2193/40	Each €	3 1	0	1 St. 199

Each €

1

Ð

KNIPEX	Double-lever	plier for	terminals
--------	---------------------	-----------	-----------

In special steel - Burnished finish - Industrial model Thermoplastic coated handles For pre-insulated terminals 0,5÷2,6 mm² Overall length 235 mm B 2193/46 Code B 2193 4600

_

B6