With automatic opening after crimping through ratchet movement KNIPEX In chrome-vanadium, hardened and oil-hardened steel - Burnished head Ergonomic and thermoplastic coated handles - With spring MM Crimping force factory calibrated - Grounded dies profiles Locking device for crimping conforming to DIN standards, unremovable for safe connections Overall lenght 250 mm Shape 3 For plug for male and female end sleeves 0,5÷6,0 mm² (AWG 20-7) With 4 notches for crimping Code B 2193 4303 B 2193/43 Each € Shape 5 For plug end sleeves (ferrules) 0,5÷6,0 mm² (AWG 20-10) width 4,8 and 6,3 mm With 3 notches for crimping Code B 2193 4305 B 2193/43 Each € Shape 6 For end sleeves (ferrules) 0,5÷6,0 mm² (AWG 20-10) With 3 notches for crimping Code B 2193 4306 B 2193/43 Each € Shape 10 For connectors COAX, BNC & TNC With 3 notches for crimping Code B 2193 4310 B 2193/43 Each €

FABC>TOOLS

Head and parts subject to crimping, in stamped chrome-molybdenum sheet metal, entirely tempered Handles coated in thick, comfortable resin - Double seam With screw for adjusting the spring Overall length 230 mm For end sleeves (ferrules) 0.5+6.0 mm² (AW(6.20-10))

Automatic crimping pliers for terminals



Insertion tool

Shock-resistant synthetic resin body - Burnished head Suitable for inserting cable in wireways and conduits, sockets and electrical panels **For UTP cables** (Unshielded Twisted Pair) **and STP** (Shielded Twisted Pair) **Ø 0,4-0,8 mm** It inserts cables in the contacts and at the same time it cuts out the remaining part With hook and release blade - Overall length 175 mm **B 2193/411 - TABC**

B 2193/421 - KNIPEX

Code B 2193 4110	B 2193/411	Each €	Ð	1
Code B 2193 4210	B 2193/421	Each €	3	1



Suitable for coax connectors F, BNC e RCA - For cables RG 59 / 6 / 11 Rotating head for different cable dimensions

 Rotating insert for adapting to different kinds of connectors

 Adjustment screw for the connector length

 Overall length 175 mm

 Code B 2193 4700

 B 2193/47





Crimping plier for Scotchlok connectors

In forged, oil tempered, vanadium steel

Thermoplastic coated handles - Polished head - 1 - With spring MM With induction-tempered cutting edges for cutting conductors For crimping resin-insulated conductors, used in the telephone sector, with U contact system in Scotchlok connectors - With parallel jaws for crimping connectors

Capacity Ø 0,4÷1,1 mm - Overall length 155 mm

Code B 2193 4800 B 2193/48



B6

6

Each €