
For unclogging sinks, bathtubs and washing machine drains etc.

For professional use with reinforced, hot-dip galvanized spiral, crushproof, rust-resistant Also suitable for unclogging medium-size industrial pipings and for heavy works

With straight, through handle with double hook - Spiral Ø 7 mm

Adjustable wooden handle with blocking bushing and wing nut - Spring with end stop Suitable for cleaning thin pipes with many curves

Code B 2337 3007	B 2337/3	Length 3 m	Each €	3	1
Code B 2337 4007	B 2337/4	Length 5 m	Each €	3	1





Spiral diameter	mm	10	12	15
Code		B 2337 5510	B 2337 5512	B 2337 5515
B 2337/55	Each €			
Head diameter	mm	40	40	60
For hoses with intern	nal Ø mm	50÷70	60÷100	100÷200

Length 10 m				
Spiral diameter	mm	10	12	15
Code		B 2337 6610	B 2337 6612	B 2337 6615
B 2337/66	Each €			
Code		-	B 2337 6012•	B 2337 6015••
B 2337/6*	Each €			
Head diameter	mm	40	40	60
For pipes with interr	nal mm	50÷70	60÷100	100÷200

^{*} Stocks low - • Head diameter 40 mm - • • Head diameter 50 mm

Extensions with male and female drive with threading 1/2" W - With plastic slip guard sleeve



Lengui 5 III				
Spiral diameter	mm	10	12	15
Code		B 2337 7710	B 2337 7712	B 2337 7715
B 2337/77	Each €			
Code		B 2337 7010	_	_
B 2337/7*	Each €			

Length 10 m

Length 10 III				
Spiral diameter	mm	10	12	15
Code		B 2337 8810	B 2337 8812	B 2337 8815
B 2337/88	Each €			
Code		B 2337 8010	_	_
B 2337/8*	Each €			

Additional heads for springs B 2337/5 - B 2337/6 - Male threaded attachment ½" W B 2337/9 - Reversed conical spiral type for hooking rags and synthetic fabrics in general B 2337/92 - Triple hook for very resistant obstructions

B 2337/92 - Triple nook for very resistant obstructions					
For spiral Ø	mm	10	12	12	15
Code		B 2337 9010	1	B 2337 9012	-
B 2337/9	Each €				
Code		_	B 2337 9212	-	B 2337 9215
B 2337/92	Each €				
External diameter	mm	30	40	50	60







With tempered steel spring, with spiral terminal - Professional version

Antidrip housing for spring in synthetic, resin reinforced with fiberglass and crank

Attachment for use with variable speed electrical drills and screwdrivers (removing the handle)				
Spring length	m	4,5	7,5	
Code		B 2337 9545	B 2337 9575	
B 2337/95	Each €			
Spring Ø	mm	6,4	8	
Locking spring		screw	screw	



