Carpenter's roofing hammers

FABC TOOLS

Forged, tempered and furnace painted head

Crab peen and smooth, polished striking

«Spain» model with slip-proof tapered handle and hollow to hold nails

B 3456 - With ash wood handle and non-magnetic hollow

B 3456/2 - With ash wood handle and magnetic holl

| b 3730/2 - Will ash wood handle and magnetic non | | | | |
|--|-------------|---|---|--|
| g | 300 | 400 | 500 | |
| | B 3456 0300 | B 3456 0400 | B 3456 0500 | |
| Each € | | | | |
| | B 3456 2300 | B 3456 2400 | B 3456 2500 | |
| Each € | | | | |
| pcs. | 6 | 6 | 6 | |
| | g Each € | g 300 B 3456 0300 Each € B 3456 2300 Each € | g 300 400 B 3456 0300 B 3456 0400 Each € B 3456 2300 B 3456 2400 Each € | |

B 3456/3 - Three-component handle: anti-slip rubber, synthetic material and fiberglass core

| b 3430/4 - In synthetic resin, reinforced with liberglass | | | | |
|---|--------|-------------|-------------|-------------|
| Weight | g | 300 | 400 | 500 |
| Code | | B 3456 3300 | B 3456 3400 | B 3456 3500 |
| B 3456/3 | Each € | | | |
| Code | | B 3456 4300 | _ | _ |
| B 3456/4 | Each € | | | |
| 3 | pcs. | 6 | 6 | 6 |
| | | | | |



| With asi wood handle - weight 200 g | | | | |
|--|----------|--------|---|---|
| Code B 3456 7000 | B 3456/7 | Each € | 3 | 6 |
| | | | | |

Spare handles

B 3456/1 - In ash wood

B 3456/40 - Three-component: anti-slip rubber, synthetic material and fiberglass core

| B 3436/5 - In synthetic resin, reinforced with liberglass | | | | | |
|---|-----------|---------------|---|----|--|
| Code B 3456 1000 | B 3456/1 | Each € | 3 | 6 | |
| Code B 3456 4000 | B 3456/40 | Each € | 3 | 20 | |
| Code B 3456 5000 | B 3456/5 | Each € | 3 | 6 | |



B 3456/2 with magnetic

hollow to hold nails

B 3456 - B 3456/2

B 3456/3

(PICARD)

Forged, tempered steel head

Two peens with different length and smooth striking head Also suitable for sheet metal workers and geologists

Ergonomic handle in rubber coated metal tube

Furnace painted head - Weight with handle 800 g

B 3457/1 - Non-magnetic hollow to hold nails - DIN 7239

B 3457/2 - Magnetic hollow to hold nails

| D 0-101/E Magnetio Hollo | ii to iioia iiaiio | | |
|--------------------------|--------------------|---------------|----------------|
| Code B 3457 1000 | B 3457/1 | Each € | > 12 |
| Code B 3457 2000 | B 3457/2 | Each € | > 12 |

Ergonomic handle in leather coated metal tube

Suitable for continuous professional use

The leather grip absorbs moisture and allows for a firm grip, offering an excellent performance with less effort during use Polished head and peen point

Magnetic hollow to hold nails

Weight with handles 970 a

| Weight With Handles 3 | ro g | | | _ |
|-----------------------|----------|--------|---|---|
| Code B 3457 4000 | B 3457/4 | Each € | 3 | 6 |
| | | | | |



B 3457/2

B 3457/4 with magnetic

hollow to

hold nails



Mechanic's hammers → C 2 pag. 302



Head in forged steel

With smooth chisel with 47 mm width suitable for making grooves in the wall, striking head and nail puller hollow

Ergonomic handle in rubber coated metal tube

Overall length 280 mm

Code B 3458 1000 B 3458/1 6 Each € 8

