


ABC TOOLS Concrete drill bits

In nickel-chrome-molybdenum steel, with welded plate - ISO 5468

For use on rotation and percussion drills

Groove for better expulsion of drilling debris

With straight cutting edges, reinforced head and asymmetrical "S" sharpening for precision holes and with optimum discharge of drilling debris - Cylindrical stem



Type for masonry

Suitable for masonry, natural and artificial stone, reinforced concrete

Blade diameter	mm	3	4	5	6	8	9	10	12	14	16
Code		B 3630 1003	B 3630 1004	B 3630 1005	B 3630 1006	B 3630 1008	B 3630 1009	B 3630 1010	B 3630 1012	B 3630 1014	B 3630 1016
B 3630/1	Each €										
Overall length	mm	70	75	85	100	120	120	120	150	150	150
Shaft diameter	mm	2,8	3,6	4,6	5,6	7,1	8,1	8,7	10	10	10

B 8

Type for granite - Burnished version - Ground

Particularly suitable for drilling holes for plugs and fastenings in marble and granite

Suitable for masonry, natural and artificial stone, reinforced concrete, ceramics, plastics, PVC and soft wood



Blade diameter	mm	3	4	5	6	6	7	8	8	9	10	10	12	13	14	15	16	18	20
Code	B 3630 ...	5003	5004	5005	5006	5061	5007	5008	5081	5009	5010	5101	5012	5013	5014	5015	5016	5018	5020
B 3630/5	Each €																		
Overall length	mm	70	75	85	100	150	100	120	200	120	120	200	150	150	150	150	150	160	160
Shaft diameter	mm	2,8	3,6	4,6	5,6	5,6	6,6	7,1	7,3	8,1	8,7	8,7	10,0	10,0	10,0	10,0	10,0	10,0	13,0

Set of bits for concrete

With number of bits	5	7	
Code	B 3630 7005	B 3630 7007	
B 3630/7	Each €		
Drill Ø x length	mm	4x75 - 5x85 - 6x100 - 8x120 - 10x120	4x75 - 5x85 - 6x100 (2 pcs.) - 8x120 - 10x120 - 12x150
Provided in		plastic case	shockproof ABS box



B 3630 /7 sz.5



B 3630 /7 sz.7

ABC TOOLS Hammer drill bits

In nickel-chrome-molybdenum steel, hardened - ISO 5468

With hard metal plate with self-centring tip, for high-precision drilling

SDS-plus shank - Ø 10 mm

Grooves with stepped spiral, high hardness grade, resistance to breakage and long life, designed specifically for drilling clean holes at high drilling speed with optimal debris removal

Suitable for masonry, natural and artificial rock, reinforced concrete



Size	Code B 3632	B 3632	Ø d mm	L1 mm	L2 mm	Size	Code B 3632	B 3632	Ø d mm	L1 mm	L2 mm	Size	Code B 3632	B 3632	Ø d mm	L1 mm	L2 mm
	Each €					Each €					Each €			
0411	0411		4,0	110	50	1016	1016		10,0	160	100	1645	1645		16,0	450	400
0416	0416		4,0	160	100	1021	1021		10,0	210	150	1660	1660		16,0	600	550
0511	0511		5,0	110	50	1026	1026		10,0	260	200	1820	1820		18,0	200	150
0516	0516		5,0	160	100	1031	1031		10,0	310	250	1830	1830		18,0	300	250
0521	0521		5,0	210	150	1046	1046		10,0	460	400	1845	1845		18,0	450	400
0611	0611		6,0	110	50	1216	1216		12,0	160	100	2020	2020		20,0	200	150
0616	0616		6,0	160	100	1221	1221		12,0	210	150	2030	2030		20,0	300	250
0621	0621		6,0	210	150	1226	1226		12,0	260	200	2045	2045		20,0	450	400
0626	0626		6,0	260	200	1231	1231		12,0	310	250	2060	2060		20,0	600	550
0711	0711		7,0	110	50	1245	1245		12,0	450	400	2100	2100		20,0	1000	950
0811	0811		8,0	110	50	1416	1416		14,0	160	100	2225	2225		22,0	250	200
0816	0816		8,0	160	100	1421	1421		14,0	210	150	2245	2245		22,0	450	400
0821	0821		8,0	210	150	1426	1426		14,0	260	200	2260	2260		22,0	600	550
0826	0826		8,0	260	200	1431	1431		14,0	310	250	2210	2210		22,0	1000	950
0846	0846		8,0	460	400	1445	1445		14,0	450	400	2445	2445		24,0	450	400
0916	0916		9,0	160	100	1516	1516		15,0	160	100	2525	2525		25,0	250	200
0926	0926		9,0	260	200	1621	1621		16,0	210	150	2545	2545		25,0	450	400
1011	1011		10,0	110	50	1631	1631		16,0	310	250	2645	2645		26,0	450	400

Set of drills with SDS-plus shank - Ø 10 mm

Complete with 7 drills B 3632

In shockproof ABS case

With number of bits	7	
Code	B 3632 7007	
B 3632/7	Each €	
Drill Ø x length	mm	5x110 - 6x110 - 6x160 - 8x110 - 8x160 - 10x160 - 12x160

