**A** 1

## Fixed blade voltage tester screwdrivers

Code H 5437 2000

H 5437/2

or voltage <b>100÷50</b> empered steel bla	de, hardene	d and nickel-plated	- 🔁 12 nrs					
Blade length	mm	45	<b>65</b>	10	0*	1	-	and the second second
Code		A 1502 1035	A 1502 106			1	A 1E0	2 1065
A 1502/1	Each €						UCI A	2 1065
Blade dimensions	mm	3x0,5	3x0,5	4x0	0,6			
Overall length	mm	120	140	19	•	]	A 150	2 1100
		VDE 0680 - For vo	oltage 120÷250\	V		CE	A 150	2 3065
empered nickel-pla Blade length	mm	65		100				
Code		A 1502 3065	5	A 1502 3100	)	1.000		
A 1502/3	Each €							
Overall length	mm	140		190		]		2 3100
	Hz - Chrom	VDE 0680 - For vo e-vanadium steel bl		V 100		<u>ر</u> د-		
Code		A 1502 4065	5	A 1502 4100	)		S A 150	2 4065
A 1502/4	Each €							
Blade dimensions	mm	3x0,4		3,5x0,4		-		
Overall length	mm	155		190		1	A 150	2 4100
	n chrome-m <b>nm</b> - Overall	e acetate - With poc olybdenum-vanadiu length 140 mm 1502/45	im steel, chrome	ed ch€	<b>3</b>		会 (4 	
Precision blade, ir	e in cellulose n chrome-m	e acetate - With poc olybdenum-vanadiu		d				
Ergonomic handle	e in cellulose n chrome-m nm - Overll le	olybdenum-vanadiu	im steel, chrome	id ch €	<b>F</b> 12		<b>(</b> A	
Ergonomic handle Precision blade, ir Blade length 70 m Code A 1502 5070 Allows checking: alternating curre hot, ground and n continuity and pol- tigh-brightness c With pocket clip - F	e in cellulose n chrome-m m - Overll le A on volta ent up to 25 neutral wires, arity on fuse control LED Powered by 3	olybdenum-vanadiu ength 142 mm 1502/5 ge tester sc 50V even contactle s, lamps, etc. to use the voltage 3 AG-3 button cells	rewdriver ess; (included) or sim	ch €	<b>3</b> 12		( 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	
Ergonomic handle Precision blade, ir Blade length 70 m Code A 1502 5070 Multifunctio Allows checking: alternating curre hot, ground and n continuity and pol- tigh-brightness o With pocket clip - F	e in cellulose n chrome-m m - Overll le A on volta ent up to 25 leutral wires, arity on fuse control LED Powered by 3 mm - Blade	olybdenum-vanadiu ength 142 mm 1502/5 ge tester sc 50V even contactle s, lamps, etc. to use the voltage	rewdriver ess; (included) or sim	ch €	<b>3</b> 12	-		
Ergonomic handle Precision blade, in Blade length 70 m Code A 1502 5070 Allows checking: alternating curres hot, ground and n continuity and pole <b>ligh-brightness o</b> With pocket clip - P Dverall length 145 f Code A 1503 0000 Code A 1503 0000 With voltage teste ED) for magnetic Support with 2 swite Court and 8 mm With ON-OFF swite Supplied with doub Powered by 2 batte Doverall length 155 m Code M 7108 9900 Contactless	e in cellulose n chrome-m m - Overll le on volta ent up to 25 eutral wires, arity on fuse control LED Powered by 3 mm - Blade control Cabi er without co c fields rel sockets v r - 1 @ x 9 r h and pocket le bit @ 7,0 eries (LR44) - mm N s voltag	olybdenum-vanadiu ength 142 mm 1502/5 ge tester sc 50V even contactle is, lamps, etc. to use the voltage 3 AG-3 button cells dimensions 15x3 m 1503 inet keys contact up to 600 m with the following so mm - 1 ♀ x 3-5 mn et clip bx1,2 mm and ♀ Pl - Automatic switch- 17108/99 e detector	Im steel, chrome Eac rewdriver ess; tester also as ins (included) or sim m Eac V (50-60 Hz) an ickets: n H 2 off after about 2 Eac	ch € spection light illar ch € id optical indica minutes inactivity ch €	tor (greer	] • • • • • •		
	e in cellulose n chrome-m m - Overll k ent up to 25 leutral wires, arity on fuse control LED Powered by 3 mm - Blade croi cabi er without co c fields vel sockets v l - 1 ( ) x 9 r h and pocket le bit ( 7,0 pries (LR44) - mm N S voltag the tensio ptions in cat om 24V to 1 ery deep line hrough LED h brightness	olybdenum-vanadiu ength 142 mm 1502/5 ge tester sc 50V even contactle s, lamps, etc. to use the voltage 3 AG-3 button cells dimensions 15x3 m 1503 inet keys contact up to 600 ° with the following so mm - 1 Q × 3-5 mn et clip lx1,2 mm and ♀ Pl - Automatic switch- 17108/99 e detector n in electrical pane bles, without contact 1000V AC - Freque a mini-torch, ON/OF	Im steel, chrome Ead rewdriver ess; tester also as ins (included) or sim m Ead V (50-60 Hz) an ockets: n H 2 off after about 2 Ead ls, cables, socket tency 50-60 Hz signal	ch € spection light nilar ch € d optical indica minutes inactivity ch € ets, circuits, lights	tor (greer	] • • • • • •		

www.abctools.it

🍞 1

Each €