Rim wrenches for heavy vehicles

Cross type with 3 hexagonal and openings square drive

Chrome-vanadium steel - Chromed version

FABC TOOLS

Electrically welded cross wrench

Opening sizes

24 x 27 x 32 mm and drive 3/4"

Overall length 690 mm

Code C 3057 0000

C 3057

Each €

Each €





Reinforced cross wrench - Forged and hardened heads and central part - DIN 3119

Opening sizes ○ 24 x 27 x 32 mm and square drive ¾"

Overall length 750 mm

Code C 3058 2000

Cross type with 4 hexagonal openings ()

Crome-vanadium steel - Chromed version

HAZET

Reinforced cross - Heads and central part forged and tempered - DIN 3119

C 3058/2

For tractors, earth moving machines, etc. - Tested to 2000 Nm

Opening 24 x 27 x 32* x 38 mm - Opening in inches 15/16 x 11/16 x 11/4 x 11/2

Overall length 750 mm

Code C 3058 3000

C 3058/3



With female square

inside the 32 mm

openina

1035÷1430 mm

 ϵ

* Inside the 32 mm opening there is a 20,64 mm square drive (13/16") particularly suitable for twin wheels of truck trailers and trailers, where a square drive is indispensable for the square of the column



With telescopic lever length from 1035÷1430 mm and square drive 3/4"

Special hardened steel, burnished version

The extra long lever makes it possible to apply high torques (up to 1200 Nm at the maximum extension) facilitating

the removal and mounting of the wheels of heavy vehicles

Can be dismantled into 3 parts to reduce overall size and also be kept in the toolbox

Safety blocking of the parts with ball retainer

With plastic handle

Rod with square drive length 445 mm suitable for reaching nuts

located at depth Code C 3058 6000

C 3058/6

Each €





FABC>TOOLS

T-type with hexagonal openings

Complete with retractable lever of length 600 mm

Overall length 430 mm - pc. 1

Opening	mm	30 x 32 (1 ³ / ₁₆ " x 1 ¹ / ₄ ")	32 x 38 (1½" x 1½")
Code		C 3059 3004	C 3059 3005
C 3059/3	Each €		

*** Hydraulic jacks

Entirely in steel - Conforming to DIN 76024

With lever handle

Jacks with capacity from 5 to 30 t have a height-adjustable head through screw

Capacity	t	3	5	10	15	20	30
Code	L 3403	0003	0005	0010	0015	0020	0030
L 3403	Each €						
Min÷max height	mm	200÷325	220÷485	240÷515	245÷515	285÷575	295÷585
Weight	kg	4,8	5,5	8	10	18	25



In steel - Suitable for car support

Large and stable base

Capacity	t	1	1	3,5
Code		L 3405 0001	L 3405 0011	L 3405 0035
L 3405	Each €			
Min÷max height	mm	280÷480	380÷650	440÷740
Base size	mm	260x260	260x260	300x300
Weight	kg	3	4	8

