### **Screw extractors**


#### Chrome-vanadium steel

Type with 4 counterposed cutting edges (2 for right-handed thread and 2 for left-handed thread) - For right and left-handed thread

With hexagonal head 
for use with wrenches

Insert the extractor into the screw with a hammer and then start extracting. When finished the screw will still have its thread intact

For screws	М	5÷6	8÷10	10÷12	12÷16	16÷20
Code		C 3294 5001	C 3294 5002	C 3294 5003	C 3294 5004	C 3294 5005
C 3294/5	Each €					
Hexagonal 🌘	mm	6,35 (1/4")	9,5 (3/8")	12,7 (½")	15,9 (5/8")	19 (¾")



# Set of extractor C 3294/5 with 4 counterposed cutting edges

In plastic case

C 3294/53 - With 3 extractors for M 5÷12 screws C 3294/55 - With 5 extractors for M 5÷20 screws

O 3234/33 - Willi 3 Extract	013 101 141 3-20 301	CWS		
Code C 3294 5300	C 3294/53	Each €	3	1
Code C 3294 5500	C 3294/55	Each €	<b>3</b>	1

# Adjustable tap wrenches in hot-pressed (forged) steel to withstand high stress

DIN 1814 - Tempered jaws

Knurled handles

Midiled Haildles						
Size		1	2	3	4	
Code	F 7982	0001	0002	0003	0004	
F 7982/0	Each €					
For square DIN	mm	2,1÷5,5	3,4÷9	4,9÷12	5,5÷16	
Suitable for taps	М	1÷10	4÷12	5÷20	9÷27	
Overall length	mm	175	260	375	480	









C 3294/55





# Roller type stud pullers

Chrome-molybdenum - Chromed version

For left and right-handed studs
internal ½" drive and external 21 mm

Uniternal /2 Univ	e and exten	nai Z i iiiii			
For shafts Ø	mm	6	8	10	12
Code		C 3295 0006	C 3295 0008	C 3295 0010	C 3295 0012
C 3295	Each €				
Overall length	mm	60	60	68	68
External Ø	mm	24	24	28	28

## Set of stud pullers

Consisting of:

4 pullers C 3295 Ø 6 - 8 - 10 - 12 mm

In metal box

Code C 3295 5000	C 3295/5	Each €	<b>3</b>	1
------------------	----------	--------	----------	---







With hexagonal handle drive 19 mm - Max. torque 120 Nm


The coplanarity of the knurled wheel base with the jaw base allows tightening of extremely short

Type for screws and studs Ø 5÷20 mm

Weight 0,4 kg

Code C 3296 4000 C 3296/4	Each <b>€</b>	<b>3</b> 1	
---------------------------	---------------	------------	--





Small size, suitable for places hard-to-reach places

For screws Ø	mm		10÷19	18÷28
Code		C 3296 7015	C 3296 7019	C 3296 7028
C 3296/7	Each €			



