

Die-cast light alloy body - Strong holding force for lifting and carrying slabs of glass, marble, plastic laminates and sheet metal with smooth non-porous surfaces

#### White suction cup ideal for not leaving marks on the surface

**Attention:** Read carefully the instructions provided with the tool before use

# Type with 1 suction cup, with reading dial for lifting

With dial for reading off low, medium and high negative pressure in Hg and central handle for regulation of the vacuum

Rapid indication of any loss of holding power - Knob for locking

Technical specifications:

recrimed specimentoris.							
Suction lifter Ø mm 180			Suction lifter Ø mm 200				
Glass	Vacuum	Hg	Weight liftable	Glass	Vacuum	Hg	Weight liftable
thickness mm	vacuum	пу	g max. kg	thickness mm	vacuum	пу	max. kg
4	low	20	100	4	low	20	100
		30				30	
		30		4.6		30	120
4÷6	medium	30	130	4÷6	medium	40	130
4-0	medium	50	130	6÷8		40	160
6÷8	high	Ε0	150	0-0	high	50	100
		50		0.10		50	190
		60		8÷10		60	
					1		

Suction cup diameter	mm	180	200
Code		C 6141 0000	C 6141 0200
C 6141/0	Each €		
Weight	kg	1,4	1,5





## Angular jointed type for mounting - With 2 suction cup lifters Ø 120 mm

Particularly suitable for forming angles from 90° to 270° Ideal for constructing shop windows, aquariums, etc.

With locking lever - Joint with screw adjustment

Weight approx. 1,2 kg

Code C 6141 2000	C 6141/2	Each <b>€</b>	<b>3</b> 1	
------------------	----------	---------------	------------	--

#### Replacement accessories kit

Consisting of: 1 rubber suction cup  $\varnothing$  120 mm, 1 locking lever, 1 fixing pin

Suitable for C 6140/1 - C 6140/2 - C 6140/3 - C 6141/2





# ABC TOOLS Caulking guns

# **Entirely in aluminium**

Finely painted version

Code C 6350 0000 C 6350	Each €	<b>&gt;</b> 1
-------------------------	--------	---------------

# Type with sheet steel body finely painted

Die-cast aluminium handle

Stable mechanism, guided well for high pressures

Strong hexagonal section push rod in sheet steel

#### Open version

Code C 6352 0000	C 6352	Each €	<b>3</b> 1
Open version with ret	ating chall		

#### Open version with rotating shel

Code C 6354 0000	C 6354	Each €	<b>3</b>	

## **Professional version**

Stable mechanism, guided well for high pressures


With aluminium cylinder - Die-cast aluminium handle finely painted

Round section push rod, sheet steel plate

Also suitable for sealant cartridges

Complete with cone and thrust plate - Overall length 225 mm

Code C 6356 0000	C 6356	Each €	<b>3</b>



# **martor** Caulk cartridge knife

#### RAPID

Strong plastic body resistant to abrasions

For left and right-handed use

Suitable for silicone cartridges

With a blade for cutting the nozzle obliquely at the desired diameter and another for cutting the bevel on the cartridge edge

Blades protected against accidents - Overall length 130 mm

 Code C 6358 0000
 C 6358
 Each €

