	tic hold e in soft synthetic 4,5 - 5,5 - 6,5 mn rews - Tip DIN 0 - rews - Tip 1 - 2 movable bit hold thout bit) 105 mn	n - 1 - 2 der for manual n	and machine us		A 1	575/1	
3 bits for slotted screws ← 4 3 bits for «PHILLIPS [®] » ↔ scr 2 bits for «POZIDRIV [®] » ↔ scr A 1575/1 - Version with rer Overall length (wit A 1575/2 - Long fixed versi Code A 1575 1000	4,5 - 5,5 - 6,5 mn rews - Tip DIN 0 - rews - Tip 1 - 2 movable bit hol thout bit) 105 mn ion - Overall leng	n - 1 - 2 der for manual n	and machine us		A 1.		
A 1575/2 - Long fixed versi Code A 1575 1000	ion - Overall leng		000				
	A 1575/1		<u>220 mm</u>			376 terens) felo
Code A 1575 2000			Each €	> 6	A 1575		
	A 1575/2		Each €	☞ 6	Allore	<i>"</i>	
MEGAPRO - Ergonomic han 3 bits for slotted screws ● 3 3 bits for «PHILLIPS [®] » screws 2 bits for «POZIDRIV [®] » screws 4 bits for «TORX [®] » screws Code A 1575 3000	3 - 4,5 - 6,5 mm s 🔂 - Tip DIN 1 - /s 🚯 - Tip 1 - 2	- 2 - 3		-	-	AUCUMO (CULIER)	
Bit holder ratchet Reversible ratchet for right/ felo - Ergonomic handle 3 bits for slotted screws 4	/left-hand, fixed u	resin with maga	izine, consisting c	of:			
3 bits for «PHILLIPS» 2 bits for «POZIDRIV®»	rews - Tip DIN 0 -	- 1 - 2				374 1/4*+35 ≱ ∯	elo 🚔
	A 1576/2	L. 185 mm	Each €	> 6			
4 bits for «TORX [®] » screws () Code A 1576 3000	A 1576/3	L. 235 mm	Each €	3 1			
Ratchet with bit h With () 1/4" drive - Magneti Suitable for direct insertion of #ABC===== With head bent at 25° for us A 1576/4 - Non-slip, two-cor 60-tooth ratchet - A 1576/5 - Comfortable hand 16-tooth ratchet - Code A 1576 4000	ic hold - For right f bits with ● 1/4" (use in hard-to-read mponent, ergono - 6° working angl dle with resin coa	drive ch spots mic handle le - Overall lengtl tting				- 0 1/4" FA	96:E
	A 1576/5		Each €	3 1 3 1			
Felo - With head bent a Body in chrome-vanadium ste 60-tooth ratchet - Minimum 6 Supplied with adapter 1 /4"	at 15° for use in h eel 5° working angle			B 1) eeo
HAZET - In forged chron Two-component ergonomic Reversible with lever - Mini	c handle - With 2 imum 18° workin	0-tooth ratche g angle	version et	-		•:>	HARRE
Overall length mm		95 A 1576 6095		6 6115	8 7	0 1/4"	
Code			1			-	
<i>Code</i> A 1576/6 Each €							
					1/4"		■ 1/4"

MAGNETIZZATORE

> 1

for 2/3 seconds and repeat several times **for demagnetizing**, use the hole marked by -

Code A 1576 8000 A 1576/8 Each €