

LUKAS Mounted points

Maximum rotational speed varies according to the overhang length (open shank length Lo) of the shank; for this reason, always refer to the table provided on each pack before using the mounted points



Arch pointed nose 520 - SP - Quality EKR-Standard (Corundum)

In indivisible pack of 20 pcs.

Shank Ø 6 mm

Ø x head height mm	5 x 10	8 x 16	10 x 20	13 x 20	20 x 32
Code	D 9555 0510	D 9555 0816	D 9555 1020	D 9555 1320	D 9555 2032
D 9555 Each €					
Grit and hardness	80 N	60 N	60 N	46 N	36 N



Conical round nose 620 - KE - Quality EKR-Standard (Corundum)

In indivisible pack of 20 pcs.

Shank Ø 6 mm

Ø x head height mm	10 x 25	16 x 32	16 x 40	20 x 32	20 x 40	25 x 70
Code	D 9556 1025	D 9556 1632	D 9556 1640	D 9556 2032	D 9556 2040	D 9556 2570
D 9556 Each €						
Grit and hardness	60 N	46 N	46 N	36 N	36 N	36 N



Spherical 580 KU - Quality NDW-Standard

In indivisible pack of 20 pcs.

Shank Ø 3 mm

head Ø mm	4	6	8
Code	D 9558 0004	D 9558 0006	D 9558 0008
D 9558 Each €			
Grit and hardness	100 Q/U	100 Q/U	100 Q/U



Spherical 580 KU - Quality EKR-Standard (Corundum)

In indivisible pack of 20 pcs.

Shank Ø 6 mm

head Ø mm	6	8	10	13	16	20	25	32
Code	D 9559 0006	0008	0010	0013	0016	0020	0025	0032
D 9559 Each €								
Grit and hardness	60 N	60 N	60 N	46 N	46 N	36 N	36 N	30 N



Spherical 580 KU - Quality NK-Ba soft (Blended Corundum)

In indivisible pack of 20 pcs.

Shank Ø 6 mm

head Ø mm	25
Code	D 9560 0025
D 9560 Each €	
Grit and hardness	24 N



Cylindrical flat 600 - ZY2 - Quality EKR-Standard (Corundum)

In indivisible pack of 20 pcs.

Shank Ø 3 mm


Ø x head thickness mm	13 x 3	16 x 4	20 x 6
Code	D 9567 0133	D 9567 0164	D 9567 0206
D 9567 Each €			
Grit and hardness	80 N	60 N	60 N



In indivisible pack of 20 pcs.

Shank Ø 6 mm

Ø x head thickness mm	16 x 4	20 x 6	25 x 6	25 x 10	32 x 8	40 x 10	50 x 10
Code	D 9568 0164	D 9568 0206	D 9568 0256	D 9568 2510	D 9568 0328	D 9568 4010	D 9568 5010
D 9568 Each €							
Grit and hardness	60 N	60 N	60 N	36 N	46 N	30 N	30 N




Cylindrical flat 600 - ZY2 - Quality NK-Ba soft (Blended Corundum)

In indivisible pack of 20 pcs.

Shank Ø 6 mm

Ø x head thickness mm	40 x 6
Code	D 9571 0406
D 9571 Each €	
Grit and hardness	24 N



Cylindrical flat 600 - ZY2 - Quality NK-Ba hard (Blended Corundum)

In indivisible pack of 20 pcs.

Shank Ø 6 mm

Ø x head thickness mm	40 x 10	50 x 10
Code	D 9569 4010	D 9569 5010
D 9569 Each €		
Grit and hardness	24 Q/U	24 Q/U



Cup 650 - TO - Quality EKR-Standard (Corundum)

In indivisible pack of 20 pcs.

Shank Ø 6 mm

Ø x head height mm	20 x 20	25 x 24
Code	D 9570 2020	D 9570 2524
D 9570 Each €		
Grit and hardness	60 N	60 N

