

FLEX Angle grinders

High-power and high-endurance motors, with high torque and low energy consumption for efficient work progress

Side handle with ergonomic design for left and right hand use

Air inlet for optimal air flow to reduce overheating

Dust-protected

Supplied with auxiliary handle, protective guard and backing flange - Discs not supplied

Mod. GWS 15-125 CIEH


With **"Constant Electronic"** for constant speed even under heavy load

KickBack Stop to shut the tool down immediately in case of jamming

6-stage speed preselection and Tri-Control switch

"Vibration Control" auxiliary handle with 40% vibration reduction

Handle with soft-grip for a secure hold

Absorbed power	W	1500
Idle speed	rpm	2800÷11000
Threaded shaft attachment		M 14
Weight	kg	2,3
Code E 1015 4125	E 1015/4	Each €  1



Ø 125 mm

Mod. GWS 15-125 CIEH


With **"Constant Electronic"** for constant speed even under heavy load

KickBack Stop to shut the tool down immediately in case of jamming

6-stage speed preselection and Tri-Control switch

"Vibration Control" auxiliary handle with 40% vibration reduction

Handle with soft-grip for a secure hold

Absorbed power	W	1700
Idle speed	rpm	11500
Threaded shaft attachment		M 14
Weight	kg	2,4
Code E 1015 6125	E 1015/6	Each €  1



Ø 125 mm

Mod. GWS 17-125 INOX

Low speed, ideal for machining stainless steel


With **"Constant Electronic"** for constant speed even under heavy load

Speed preselection according to the material to be machined

KickBack Stop to shut the tool down immediately in case of jamming

"Vibration Control" auxiliary handle with 40% vibration reduction

Handle with soft-grip for a secure hold

Absorbed power	W	1700
Idle speed	rpm	2200÷7500
Threaded shaft attachment		M 14
Weight	kg	2,4
Code E 1015 7125	E 1015/7	Each €  1




Ø 125 mm

Mod. GWS 22-230 JH

With Tri-Control switch, restart protection and starting current limitation

Armoured coils that protect the motor against sharp grinding dust

Absorbed power	W	2200
Idle speed	rpm	6500
Threaded shaft attachment		M 14
Weight	kg	5,2
Code E 1019 1230	E 1019/1	Each €  1



Ø 230 mm

Mod. GWS 24-230 LVI


With rotating bow handle

KickBack Stop to shut the tool down immediately in case of jamming

Both handles are equipped with **"Vibration Control"** to reduce vibration significantly for less-fatigue working

With restart protection

Starting current limitation for soft start without overload

Absorbed power	W	2400
Idle speed	rpm	6500
Threaded shaft attachment		M 14
Weight	kg	5,5
Code E 1019 4230	E 1019/4	Each €  1



Ø 230 mm

