

## ABC TOOLS Grinding wheel dressing sticks

### In silicon carbide, grey

For dressing and reshaping grinding wheels

#### With wood handle

Coarse grit 36

Abrasive diameter 20 mm - Dressing length 200 mm - Overall length 380 mm

Code D 9847 0000	<b>D 9847</b>	Each €	 15
------------------	---------------	--------	--



#### Without handle

##### Round version ●

Diameter	mm	20	20	25
Code		D 9848 1002	D 9848 1003	D 9848 1004
<b>D 9848/1</b>	Each €			
Overall length	mm	150	200	200



##### Rectangular version ■

Dimensions LxDxh 150x20x15 mm

Code D 9848 2000	<b>D 9848/2</b>	Each €	 10
------------------	-----------------	--------	--

D 8

## ABC TOOLS Diamond grinding wheel dressers

For dressing grinding wheels and for internal, external and centerless grinding

**Excellent quality diamond** perfectly set, with regular shape and well shaped centers

With hexagon head to periodically turn the dresser (to prevent the tip from flattening) and position it - Mounted on a conical bushing with Morse taper 1

Use: position at a 15° angle to the axis of the wheel to be dressed (past the center), and perform wet dressing with max depth 0,025/0,03 mm

Supplied in package with protective case

Carats		0,20	0,25	0,30	0,40	0,50	0,60	0,75
Code	D 9850 ...	0020	0025	0030	0040	0050	0060	0075
<b>D 9850</b>	Each €							
For wheels	Ø mm	125			150÷250			
Carats		0,80	1,00	1,50	2,00	2,50	3,00	
Code	D 9850 ...	0080	0100	0150	0200	0250	0300	
<b>D 9850</b>	Each €							
For wheels	Ø mm	150÷250	300÷400	400÷500		> 500		



## LUKAS Cup wheels

For use with portable grinders

High stock removal rates, long lifetime, low vibrations and noise levels, aggressive cut



#### With diameter 80 mm


For maximum operating speed 45 m/s = 12000 rpm

Grit 36 (medium)

**D 9852/1 - Normal corundum** - For steel and metals in general

**D 9852/2 - Silicon carbide** - For natural and artificial stones

Code D 9852 1036	<b>D 9852/1</b>	Each €	 5
Code D 9852 2036	<b>D 9852/2</b>	Each €	 5




#### With diameter 110 mm

For maximum operating speed 50 m/s = 8600 rpm

##### D 9852/5 - Normal corundum

For weld seams, grinding in corners and edges, steel sheets and railway tracks -  10 pcs.

##### D 9852/6 - Silicon carbide

For ductile cast iron pipes, reinforced concrete, roof tiles, bricks, ceramics, general, artificial and dressedstone, steel and iron castings, marble -  10 pcs.

Grit		16	24	80	120
Code		D 9852 5016	D 9852 5024	—	—
<b>D 9852/5</b>	Each €				
Code		—	—	D 9852 6080	D 9852 6120
<b>D 9852/6</b>	Each €				
Grain type		very coarse	coarse	fine	fine

