

**Version with 25+1 settings to adjust torque** for precision drilling

Right/left rotation

With **ECP (Electronic Cell Protection)** offering protection against overload, overheating and deep discharge

Electronic switch for perfect speed adjustment according to drilling requirements

Sturdy body with soft-grip zone for greater comfort and built-in bit holder

Self-locking chuck, opening 1,5÷10 mm

Supplied in a plastic carrying case **with 2 batteries and quick charger**

Battery	V	14,4 (1,5 Ah)	18 (1,5 Ah)
Code		E 0970 1144	E 0970 1018
<b>E 970/1</b>	Each €		
Model		GSR 1400-LI	GSR 1800-LI
Idle speed	rpm	1st 0÷420 / 2nd 0÷1400	1st 0÷400 / 2nd 0÷1300
Max. torque	Nm	30 (16 for soft materials)	34 (18 for soft materials)
Max steel drilling Ø	mm	10	10
Max wood drilling Ø	mm	25	29
Weight with battery	kg	1,3	1,4



14,4 V  
1,5 Ah

18 V  
1,5 Ah

#### Mod. GSR 18V-LI

Extremely compact due to short design and low weight for perfect handling

High-performance 4-pole motor: up to 67 Nm

**"CoolPack" technology Lithium battery:** ensures optimum heat dissipation and increases lifetime (up to 100% compared to other batteries)


With **ECP (Electronic Cell Protection)** offering protection against overload, overheating and deep discharge

Sturdy body with soft-grip zone for greater comfort

Self-locking chuck, opening 1,5÷13 mm

With motor brake for precise work when driving rows of screws and belt clip

Supplied in a **L-Boxx carrying case with 2 batteries and quick charger**

Battery	V	18 (4,0 Ah)
Idle speed	rpm	1st 0÷500 / 2nd 0÷1700
Max. torque	Nm	67 (28 for soft materials)
Tightening torque settings		18 + 1
Max steel drilling Ø	mm	13
Max wood drilling Ø	mm	35
Max screw Ø	mm	8
Weight with battery	kg	1,8
<b>Code E 0970 3018</b>	<b>E 970/3</b>	Each €  1



18 V  
4,0 Ah

#### Mod. GSB 18V-LI

**Integrated impact drilling function** for drilling in masonry up to 13 mm

Compact due to short design and low weight for perfect handling

High-performance 4-pole motor: up to 67 Nm

**"CoolPack" technology Lithium battery:** ensures optimum heat dissipation and increases lifetime (up to 100% compared to other batteries)


With **ECP (Electronic Cell Protection)** offering protection against overload, overheating and deep discharge

Sturdy body with soft-grip zone for greater comfort

Self-locking chuck, opening 1,5÷13 mm

With motor brake for precise work when driving rows of screws and belt clip

Supplied in a **L-Boxx carrying case with 2 batteries and quick charger**

Battery	V	18 (4,0 Ah)
Idle speed	rpm	1st 0÷500 / 2nd 0÷1700
Max. torque	Nm	67 (28 for soft materials)
Max strokes/min		25500
Tightening torque settings		18 + 1
Max steel drilling Ø	mm	13
Max masonry drilling Ø	mm	13
Max wood drilling Ø	mm	35
Max screw Ø	mm	8
Weight with battery	kg	1,9
<b>Code E 0971 3018</b>	<b>E 971/3</b>	Each €  1



18 V  
4,0 Ah