


**BOSCH** Circular saw

**GKS 65 GCE**

High-power hand-held circular saw with 800W motor, light and compact  
 Fast sawing due to **"Constant Electronic"**  
 Electronic regulation of speed and pre-selection - With dust collection attachment  
 Continuously variable cutting depth setting up to 65 mm for 90° and 48 mm for 45°  
 With built-in guide rail

Supplied in a L-Boxx carrying case with 1 wood saw blade Ø 190x2,0 mm with 30 teeth per inch

Blade Ø x hole	mm	190 x 30
Absorbed power	W	1800
Idle speed	rpm	2300÷5000
Weight	kg	5,2
<b>Code E 1033 3190</b>	<b>E 1033/3</b>	Each €  1




CE

**BOSCH** Shear

**GSC 75-16**

Powerful and handy for fast and comfortable cutting  
 Optimal tool guidance with a small grip circumference and excellent manoeuvrability in curves  
 Easy to change 4-sided cutting blade  
 With chip deflector  
 Max cutting capacity: steel 400N/mm<sup>2</sup> 1,6 mm / 600 N/mm<sup>2</sup> 1,2 mm / 800 N/mm<sup>2</sup> 0,7 mm  
 aluminium 200 N/mm<sup>2</sup> 2,2 mm

Absorbed power	W	750
Idle stroke		5200
Smallest radius	mm	35
Weight	kg	1,7
<b>Code E 1035 1000</b>	<b>E 1035/1</b>	Each €  1




CE

**BOSCH** Nibbler

**Mod. GNA 2,0**

Slim, narrow design for optimum handling  
 For interior cut-outs, also with templates  
 Lockable die plate for straight cuts, swivel-mounted for better manoeuvrability in corners  
 Easy-to-change cutting tools  
 Supplied **with die plate and punch**

Absorbed power	W	500
Idle stroke		2400
Max steel thickness	mm	2 (400 N/mm <sup>2</sup> )
Smallest radius	mm	3
Cutting track width	mm	6
Weight	kg	2
<b>Code E 1037 5000</b>	<b>E 1037/5</b>	Each €  1



CE

**BOSCH** Detector

**Mod. GMS 120**

Multi-detector for ferrous and non-ferrous metals, live cables and wooden studs  
 Automatic calibration, reliable detection of objects due to three-colour LED luminous ring  
 Pinpoint indication of the object's centre and display of material properties

**Max. detection depth:**

- steel 120 mm / non-ferrous metals 80 mm

- live cables 50 mm / wooden studs 38 mm

Power supply by a 9V battery, included - Operating time approx. 5h

Automatic switch-off after approx. 5 min. - Weight 270 g

Supplied **with carrying case and wrist strap**

<b>Code E 1045 1000</b>	<b>E 1045/1</b>	Each €  1
-------------------------	-----------------	--

CE



IP 54



BOSCH laser distance meter → H 5 pag. 667

BOSCH self-levelling laser levels → H 6 pag. 678