

## ABC TOOLS Extension sockets

With **6 10/16A Schuko sockets, transversal (45°)** to facilitate plug insertion, **ON/OFF safety switch** with light and 16A bipolar plug

**E 1067/8 - Standard type**, in plastic



With cable length 1,4 m - Overall length 340 mm

**E 1067/9 - Professional type with anodized aluminium body**

Suitable for EDP, PC, peripherals, video systems, etc.

Cable length 3 m, section 3x1,5 mm<sup>2</sup>

With holes to hang on wall - Overall length 430 mm

Code E 1067 8000	<b>E 1067/8</b>	Each €		1
Code E 1067 9000	<b>E 1067/9</b>	Each €		1

CE



E 1067/8



E 1067/9

## ABC TOOLS 4-way power distributor

Suitable for construction sites, industry etc.

Strong block in thermoplastic material, shockproof and unbreakable

With **4 CEE 3-pins sockets 230V and CEE plug 230V**

Cable length 5 m, section 3x1,5 mm<sup>2</sup>

**Protection level IP 44** - With swivel hook for hanging

Code E 1071 1000	<b>E 1071/1</b>	Each €		1
------------------	-----------------	--------	---	---

IP  
44

CE

## ABC TOOLS Portable distribution board

Suitable for construction sites, industry, to supply small electrical appliances etc.

Entirely in shockproof thermoplastic material with carrying handle

**For 230V voltage** - Manufactured according to EN 61242 - EN 60439-1 (CEI 17-13) standards

**Protection level IP 44**

Supplied with **2 m connection cable with 3-pins plug (2 phase 230V + earthing) 16A** according to CEE standards

**Panel with 4 CEE 3-pin sockets** with self-closing covers

Automatic thermal-magnetic cut-off single phase residual-current device 230V / 16A / 30mA, with protective cover

Overall dimensions LxDxH 275x130x360 mm

Code E 1072 0000	<b>E 1072</b>	Each €		1
------------------	---------------	--------	---	---



CE

IP  
44

## SCANGRIP® Work lights for construction sites

INNOVATION FROM DENMARK

**Sturdy body in die-cast aluminium**, thin design with shockproof rubber profile

Suitable for use in construction sites even in difficult conditions: dirty, wet, outdoors, in all weather conditions

With COB LED which provides even and constant lighting with high CRI (Colour Rendering Index) value

**Dimmer function to adjust the light to 5 different levels: 10% - 25% - 50% - 75% - 100%**

With integrated handle to transport the lamp and adjustable rear support to position it with the best lighting angle for direct installation on the tripod

**Mod. NOVA 3K C+R**

**300÷3000 lumen (10%÷100%)** - 5000 lux at 0÷5 m


Operating time 1÷14 h

Rechargeable Li-ion battery 11,1V (4400 mAh)

Charging time aprox. 2 h

Provided with 5 m power cable for power supply from mains at 100-240 V/AC 50-60 Hz with Schuko plug

Dimensions 235x233x88 mm - Weight 1,8 kg

Code N 9125 3000	<b>N 9125/3</b>	Each €		1
------------------	-----------------	--------	---	---

**Mod. NOVA 3K C+R**

**500÷5000 lumen (10%÷100%)** - 8000 lux at 0,5 m


Autonomy 1÷12 h

Rechargeable Li-ion battery 11,1V (5200 mAh)

Charging time approx. 2h

Provided with 5 m power cable for power supply from mains at 100-240 V/AC 50-60 Hz with Schuko plug

Dimensions 267x262x87 mm - Weight 2,1 kg

Code N 9125 5000	<b>N 9125/5</b>	Each €		1
------------------	-----------------	--------	---	---


IP  
67IK  
07Rechargeable  
batteryIP  
67IK  
07Rechargeable  
battery