FLEX Cordless drills

Robust gearbox housing made of die-cast aluminium with ergonomically designed, non-slip, soft grip handle

Electronic Management System (EMS) protects the machine, extends the service life, and increases efficiency - Right/left rotation with safety catch

2-speed, impact function and electronic quick-acting brake

LED lamp for work area illumination and night light function

With 10,8V battery

With motor without carbon brushes, high efficiency and long life

Quick-locking chuck, opening 1,5÷13 mm

Suitable for use with all 10,8V batteries

Supplied in a carryng case complete with belt clip and bit holder - Without battery and charger

For batteries	٧	10,8			
Max. torque	Nm		1st speed 32 / 2nd speed 58		
Nr. of torque positions		24 + 1 Drill			
Idle speed	rpm	1st speed 0 ÷ 450 / 2nd speed 0 ÷ 1700			
Idle impacts/min		1st speed 0 ÷ 5850 / 2nd speed 0 ÷ 22100			
Weight	kg	1,1			
Code E 1090 0108		E 1090	Each €		1



 ϵ

With 18V battery

With high-performance and high-endurance 4-pole motor

Self-locking metal chuck with ring and automatic lock, opening 1,5÷13 mm

Suitable for use with all 18V batteries

Supplied in a carrying case complete with 2 18V - 2,5 Ah batteries, charger, auxiliary handle,

clin and hit holder - Without batte

beit clip and bit holder - Without battery and charger					
Battery	٧	18			
Max. torque	Nm	1st speed 52 / 2nd speed 65			
Nr. of torque positions	ositions 24 + 1 Drill				
Idle speed	rpm	1st speed 0 ÷ 380 / 2nd speed 0 ÷ 1650			
Idle impacts/min		1st speed 0 ÷ 4940 / 2nd speed 0 ÷ 21450			
Weight (excluding battery) kg	1,4			
Code E 1090 1018		E 1090/1	Each €	8	



Li-ion batteries for **FLEX** battery-powered tools

With patented cooling system and remaining charge indicator

Protected against dust and water splashes

Electronic Management System (EMS) protects the battery, extends the service life, and increases efficiency

Type with 10,8V voltage

Capacity	Ah	2,5 (10,8V)	4,0 (10,8V)
Code		E 1090 7825	E 1090 7804
E 1090/78	Each €		

Type with 18V voltage

Capacity	Ah	2,5 (18 V)	5 (18 V)
Code		E 1090 8025	E 1090 8005
E 1090/8	Each €		

Battery charger for Li-ion 10,8V and 18,0V batteries

With battery cooling system, protection against overheating, electrical shock and overload Wide LCD display for battery diagnostics and charge levels

Charging time: approx. 40 min. for 18,0V / 2,5 Ah and approx. 50 min. for 18,0V / 5,0 Ah

Charges 80% of the capacity after about 30 min

Code E 1090 9000	E 1090/9	Each €	3	1
				_













Set of bits

2 bits for PHILLIPS® screws - Tip DIN 1 - 2 2 bits for POZIDRIV® screws - Tip 1 - 2

3 bits for screws with hexagonal socket 3 - 4 - 5 mm 5 bits for TORX® screws 7110 - T15 - T20 - T25- T30

1 magnetic bit holder adapter with drive 1/4" and quick release sliding holder

Supplied in plastic case

Code A 1596 1500 **Torsion** A 1596/15 Each €





bits