ABC TOOLS Impact drill

Electronic-reversible - Clockwise and counter-clockwise rotation
Gun-shaped handle with two rotation speeds
With self-locking chuck opening 0÷13 mm - Attachment ½" x 20 UNF
Supplied in synthetic resin case, with compartment for different accessories and additional handle and depth limit gauge for graded drilling

Power	**W**	**1100**
Nr. rotation speeds		2
Idle speed	rpm	1st speed 0 ÷ 1000 / 2nd speed 0 ÷ 3000
Impact strokes/min		1st speed 16000 / 2nd speed 48000
Max steel drilling Ø	mm	13
Ø concrete drilling max.	mm	16
Ø wood drilling max.	mm	40
Weight	kg	2,7
Code E 1091 1100	**E 1091/11**	Each **€** — 1

Self-locking chucks ⟶ E 4 pag. 460

FLEX Hammer drills

Universal hammer drill for drilling, impact drilling in concrete and in walls Ø 4÷18 mm, for through-holes and dowel fixings, suitable also for light-duty chiselling works when removing plaster and tiles
With functions converter, blocking switch and speed controller
SDS-plus tool attachment
Clockwise and counter-clockwise rotation with switchover via carbon brush reverser
With non-slip handle for a safe grip and additional rotating handle with integrated depth limit gauge
To drill: concrete Ø max. 26 mm - steel Ø max.13 mm - wood Ø max. 30 mm
Supplied with case for carrying, with additional handle and depth limit gauge

Absorbed power	**W**	**800**
Idle speed	rpm	0 ÷ 1300
Idle impact strokes/min		0 ÷ 4000
Single stroke	J	2,7
Max steel drilling Ø	mm	13
Ø concrete drilling max.	mm	26
Ø wood drilling max.	mm	30
Weight	kg	2,6
Code E 1097 1000	**E 1097/1**	Each **€** — 1

Hammer drill / chisel hammer

Drill bits with 5 cutting edges
Suitable for concrete, bricks, natural and artificial stone etc.
With 1 central cutting edge and 4 cutting edges on the circumference in special quality hard metal
SDS-plus attachment - Ø 10 mm

Size		**1625**	**1645**	**1825**	**1845**	**2025**	**2045**	**2225**	**2245**	**2445**	**2545**	**2845**	**3045**
Code	***B 3660 ....***	***1625***	***1645***	***1825***	***1845***	***2025***	***2045***	***2225***	***2245***	***2445***	***2545***	***2845***	***3045***
B 3660	Each **€**												
Ø d	mm	**16**	16	**18**	18	**20**	20	**22**	22	**24**	**25**	**28**	**30**
Length L¹	mm	250	450	250	450	250	450	250	450	450	450	450	450
Length L²	mm	200	400	200	400	200	400	200	400	400	400	400	400

B 8 ⟶ pag. 240

Combined version impact drill/chisel hammer - SDS-max tool attachment
With impact drilling and only impact functions
Ideal for removing plaster and coatings from walls and concrete surfaces, for making anchoring holes and through holes
With **anti-vibration, non-slip, ergonomic handle** for a higher comfort and additional handle with depth limit gauge
Service light indicating when the carbon brushes need to be replaced
Selector for the commutation of hammer drilling and chiselling functions and variable speed drive
Supplied with transport case, with additional handle, depth limit gauge and grease tube

Absorbed power	**W**	**1050**
Idle speed	rpm	0 ÷ 380
Idle impact strokes/min		1300 ÷ 2900
Single stroke	J	10
Chiselling adjustment	n°	12
Concrete drilling	mm	40
Ø mansory drilling max.	mm	90
Weight	kg	6,4
Code E 1097 2000	**E 1097/2**	Each **€** — 1

Impact drill / chisel hammer

Hammer drill bits with 5 cutting edges ⟶ B 8 pag. 240