

FLEX Straight grinders

Suitable for abrasive mounted points, flap brushes, polishing discs and cotton fiber discs
Electronics with continuous pre-selection of the number of revolutions/rpm and overload protection



«MINI» type with collet - High speed

With 2 service wrenches and tightening collet with nut

Mounted points max Ø	mm	50
Absorbed power	W	710
Idle speed	rpm	10000 ÷ 30000
Tool attachment	Ø	3, ¼", 6, 8 mm
Head length		Ø 40 mm - length 60 mm
Total length	mm	325
Weight	kg	1,8
Code E 1112 5000	E 1112/5	Each € 1



Electronic

«MINI» type with collet - Low speed

With 2 service wrenches and tightening collet with nut

Mounted points max Ø	mm	50
Absorbed power	W	710
Idle speed	rpm	2500 ÷ 6500
Tool attachment	Ø	3, ¼", 6, 8 mm
Head length		Ø 50 mm - length 53 mm
Total length	mm	330
Weight	kg	2,1
Code E 1113 1000	E 1113/1	Each € 1



Electronic

Mounted points with shank Ø 6 mm - Cylindrical 510 - ZY

Quality EKR-Standard (Corundum)

In indivisible pack of 20 pcs.

Ø x head height	mm	6 x 10	8 x 10	10 x 13	10 x 20	13 x 20	16 x 20	16 x 32	20 x 20	25 x 25	32 x 32	40 x 20
Code	D 9544	0610	0810	1013	1020	1320	1620	1632	2020	2525	3232	4020
D 9544	Each €											
Grit and hardness		60 N	60 N	60 N	60 N	46 N	46 N	46 N	36 N	36 N	30 N	30 N

D 5 → pag. 397



Combined type with abrasive fabric fins and abrasive fabric of synthetic fibres in corundum (dark red)

This particular abrasive fabric, in an elastic laminated layers, makes it possible to finish surfaces with good removal
Suitable for use on steel, tempered steel, steel alloys, tool steel, rustproof and acid proof steel, cast iron, plastics, wood and rubber

Diameter x height	mm	40x20	50x20	50x30	60x30	80x40
Code	D 9674	4020	5020	5030	6030	8040
D 9674 - Grit A 104/80 (medium)	Each €					
Code	D 9675	4020	5020	5030	6030	8040
D 9675 - Grit A 106/150 (fine)	Each €					
Max rotational speed	rpm	14000	11000	11000	9000	7000

D 5 → pag.407



FLEX Angle grinders

Light version for precision works with minimum effort and great value for money

Carbon brushes with automatic stop before complete wear

With locking button on the grinding wheel holder shaft

Supplied with additional handle for left and right hand use, protection cover and fixing flange
Without discs



For discs Ø 115 mm

Absorbed power	W	750
Idle speed	rpm	11000
Threaded shaft attachment		M 14
Weight	kg	1,8
Code E 1113 2000	E 1113/2	Each € 1



Ø 115 mm

For discs Ø 125 mm

Absorbed power	W	800
Idle speed	rpm	11000
Threaded shaft attachment		M 14
Weight	kg	1,8
Code E 1113 3000	E 1113/3	Each € 1



Ø 125 mm

Cutting discs for portable machines → D 7 pag. 421