

ABC TOOLS Self-locking chucks

With 3 jaws - Steel body, tempered jaws

Industrial type for portable drills

E 1120/1 - With threaded attachment - 3/8" x 24 UNF

E 1120/2 - With threaded attachment - 1/2" x 20 UNF

E 1120/3 - With conical attachment DIN 238/2 (for attachments see G 900/1 - G 900/2)

| For drills up to Ø | mm | 10 | 13 |
|------------------------|----------|-------------|-------------|
| Code | | E 1120 1010 | — |
| E 1120/1 | Each € | | |
| Code | | E 1120 2010 | E 1120 2013 |
| E 1120/2 | Each € | | |
| Code | | E 1120 3010 | E 1120 3013 |
| E 1120/3 | Each € | | |
| Minimum opening | mm | 1 | 1 |
| DIN 238/2 attachment | E 1120/3 | B 12 | B 16 |
| Length closed | mm | 70 | 85 |
| External diameter max. | mm | 36 | 49 |



E 1120/1 - E 1120/2 - Threaded attachment



E 1120/3 - Conical attachment

Industrial type with locking ring for hammer impact drills

With threaded attachment - 1/2" x 20 UNF

Safety version, particularly suitable for use on portable hammer impact drills

With ring for blocking the tightening force and double protection against dust infiltrations

| For drills up to Ø | mm | 13 |
|------------------------|--------|-------------|
| Code | | E 1120 4013 |
| E 1120/4 | Each € | |
| Minimum opening | mm | 1 |
| Length closed | mm | 104 |
| External diameter max. | mm | 46 |



Threaded attachment

Heavy type for column and radial drills, lathes and milling machines

E 1120/5 - With conical attachment DIN 238/2 - B 12

E 1120/6 - With conical attachment DIN 238/2 - B 16

E 1120/7 - With conical attachment DIN 238/2 - B 18

| For drills up to Ø | mm | 10 | 13 | 16 |
|------------------------|--------|--------------|-------------|-------------|
| Code | | E 1120 5010* | — | — |
| E 1120/5 | Each € | | | |
| Code | | E 1120 6010 | E 1120 6013 | E 1120 6016 |
| E 1120/6 | Each € | | | |
| Code | | — | — | E 1120 7016 |
| E 1120/7 | Each € | | | |
| Minimum opening | mm | 1 | 1 | 1 |
| Closed length | mm | 89 | 91 | 111 |
| Max. external diameter | mm | 40,5 | 42,5 | 48 |

* E 1120/5: length closed 81 mm - Max external diameter 44 mm



Conical attachment

Heavy-industry and precision type

For column and radial drills, lathes and milling machines

With threaded attachment - 1/2" x 20 UNF

| For drills up to Ø | mm | 13 |
|------------------------|--------|-------------|
| Code | | E 1120 7513 |
| E 1120/75 | Each € | |
| Minimum opening | mm | 1 |
| Length closed | mm | 94 |
| External diameter max. | mm | 51 |



Threaded attachment

ABC TOOLS "Wescott" chucks

With 2 jaws - Conical attachment DIN 238/2 - To tighten drill bits, drills, auger bits and mills for wood

| Max opening Ø | mm | 16 | 20 | 26 |
|----------------------|--------|-------------|-------------|-------------|
| Code | | G 0860 0016 | G 0860 0020 | G 0860 0026 |
| G 860 | Each € | | | |
| Attachment DIN 238/2 | | B 18 | B 22 | B 24 |
| External Ø | mm | 54 | 61 | 70 |
| Overall length | mm | 70 | 76 | 93 |
| drive for wrench | mm | 7 | 8 | 8 |



DIN 238/2 coupling