

Impact wrenches



Ultra-light magnesium body with thermoinsulated handle

With **powerful double hammer mechanism** and control to invert the rotation, that can be activated with one hand - Impact regulation in different positions for right and left rotation
Back air expulsion through handle - **Reversible**

For bolts up to **M 16** - Threaded coupling 1/4" Gas hoses with internal Ø 10 mm

Max working torque: suggested 881 Nm - tightening 1054 Nm - untightening 1700 Nm

Max idle rpm 8000 - Air consumption 2,314 l/sec

Idle noise 96 dB(A) - Idle vibrations 10,2 m/s² - Weight 2 kg

Code E 1126 1700	E 1126/17	Each €	1
-------------------------	------------------	--------	---

Type with short head (113 mm) and powerful "Jumbo Hammer" mechanism

Extremely compact and handy design for working in hard-to-reach places

Percussion regulation in different positions for right and left rotation - The lever for the power regulation can be placed on both sides, making it suitable for both left and right-handed people



For bolts up to	M	16	16
Code		E 1126 1800	E 1126 1900
E 1126	Each €		
Suggested working torque	Nm	678	620
Max tightening torque	Nm	678	745
Max loosening torque	Nm	1100	1400
Idle speed	rpm	10000	9000
Air consumption	l/sec	2,11	2,25
Idle noise	dB(A)	97,1	92,7
Idle vibration	m/s ²	9,57	8,74
Weight	kg	1,2	1,3



Transparent silicone protective cover

Protects the E 1126/18 - E 1126/19 impact wrench housing against damage during tough day-to-day workshop operations - Tool-free assembly

Code E 1126 2200	E 1126/22	Each €	1
-------------------------	------------------	--------	---



For bolts up to	M	16
Code		E 1126 2100
E 1126/21	Each €	
Suggested working torque	Nm	630
Max. tightening torque	Nm	1085
Idle speed	rpm	9500
Air consumption	l/sec	2,26
Idle noise	dB(A)	98,7
Idle vibration	m/s ²	8,6
Weight	kg	1,2

ABC - AUTOMOTIVE LINE

Aluminium body - Back air expulsion- **Reversible**

For bolts up to **M 16** - Threaded coupling 1/4" Gas for hoses with internal Ø 10 mm

Working torque 108÷339 Nm - Max tightening torque 366 Nm

Impacts/min 1100 - Max idle rpm 7500 - Air consumption 14 l/sec

Idle noise 88 dB(A) - Idle vibrations 5,7 m/s² - Weight 2,5 kg

Code E 1126 2016	E 1126/2	Each €	1
-------------------------	-----------------	--------	---

Light body in composite material and nylon fiber, high-resistant, with thermoinsulated handle
With **powerful double hammer mechanism**

Percussion regulation in 3 positions for right rotation - **Reversible**

Back air expulsion through handle

Threaded coupling 1/4" Gas hoses with internal Ø 10 mm

For bolts up to **M 16**

Working torque 813 Nm - Max tightening torque 1288 Nm

Impacts/min 1000 - Max idle rpm 7500 - Air consumption 2,1 l/sec

Idle noise 85,8 dB(A) - Idle vibrations 8,4 m/s² - Weight 2 kg

Code E 1126 2500	E 1126/25	Each €	1
-------------------------	------------------	--------	---

Set of impact wrenches and sockets accessories ○ 1/2"

Consisting of:

1 impact wrench E 1126/25

10 hexagonal impact sockets A 3223/18 12 - 13 - 14 - 15 - 16 - 17 - 18 - 19 - 21 - 22 mm

3 long hexagonal impact sockets A 3223/24 17 - 19 - 21 mm, with protective external coating

1 125 mm extension

1 universal joint

In synthetic resin case, dimensions LxDxh 420x365x80 mm - Weight 5,7 kg

Code E 1126 3000	E 1126/3	Each €	1
-------------------------	-----------------	--------	---

1 m³ per min = 1000 liters/min = 16,6 l/sec - Operating pressure 5,9÷6,2 bar



■ 1/2" drive



Reverse gear with one hand



E 1126 1800



With short head



E 1126 1900



With short head

