

## Pneumatic angle grinder

**HAZET**

Short version with body in thermoinsulated composite material and ergonomic handle  
Start-up lever with safety lock

**With 2 rings: one to select the direction** for a more ergonomic and safer work, allowing for the control of the sparks direction **and the other one for adjusting continuous speed**

Threaded coupling 3/8" Gas for hoses with internal Ø 10 mm

**For discs with max Ø 76 mm** and hole Ø 10 mm (see D 9818/10)

Idle rpm 18000 - Power 0,52 W - Air consumption 1,9 l/sec

Idle noise 88,7 dB(A) - Idle vibrations 1,8 m/s<sup>2</sup>


Overall length 207 mm - Weight 0,9 kg - Supplied disc

<b>Code E 1128 6000</b>	<b>E 1128/6</b>	Each €	 1
-------------------------	-----------------	--------	---


**LUKAS ROTTLUFF**
**Cutting discs**

MINI cutting disc for stainless steel - INOX - Mod. PREMIUMFLEX

With hole Ø 10 mm

Ø x thickness	mm	50 x 1,0	76 x 1,0	76 x 2,0	76 x 3,0
<b>Code</b>		<b>D 9818 1001</b>	<b>D 9818 1002</b>	<b>D 9818 1003</b>	<b>D 9818 1004</b>
<b>D 9818/10</b>	Each €				
Rotational speed	rpm	30500	20100	20100	20100
	pcs.	50	50	25	25



D 7 → pag. 422

### HEAVY INDUSTRIAL LINE

Body in thermoinsulated composite material with ergonomic handle

High torque engine, ideal for excellent grinding works

Additional handle with anti-vibration structure and distance air exhaust pipe

Start-up lever with safety lock

Threaded coupling 3/8" Gas for hoses with internal Ø 13 mm

**For discs max Ø 115 mm** - Threaded attachment M 14

Idle rpm 12000 - Power 1 kW - Air consumption 26 l/sec

Idle noise 88,7 dB(A) - Idle vibrations 1,2 m/s<sup>2</sup>

Overall length 244 mm - Weight 2 kg - Supplied without disc

<b>Code E 1129 0000</b>	<b>E 1129/0*</b>	Each €	 1
-------------------------	------------------	--------	---

\* to be discontinued



Body in thermoinsulated composite material with ergonomic handle

High torque engine ideal for excellent grinding results

With back air expulsion and muffler - Threaded attachment M 14

Threaded coupling 3/8" Gas

Supplied without disc

For discs max Ø	mm	115	178	230
<b>Code</b>		<b>E 1129 1115</b>	<b>E 1129 1178</b>	<b>E 1129 1230</b>
<b>E 1129/1</b>	Each €			
Idle speed	rpm	13000	8500	6500
Power	kW	0,55	1,1	1,1
Air consumption	l/sec	10,8	16,7	16,7
For hoses with internal Ø	mm	10	13	13
Idle noise	dB(A)	83	82	82
Idle vibrations	m/s <sup>2</sup>	3	2,6	3,6
Total length	mm	267	307	307
Weight	kg	1,8	3,1	3,1



### HEAVY INDUSTRIAL LINE

Metal body with additional anti-vibration handle and distance air exhaust pipe

Start-up lever with safety lock

Threaded coupling 3/8" Gas for hoses with internal Ø 13 mm

Power 1,1 kW - Threaded attachment 3/8" - Air consumption 18 l/sec

Overall length 446 mm - Weight 4,2 kg

Supplied without disc

For discs max Ø	mm	180	230
<b>Code</b>		<b>E 1129 2180</b>	<b>E 1129 2230</b>
<b>E 1129/2*</b>	Each €		
Idle speed	rpm	7500	6000
Idle noise	dB(A)	91,7	85,9
Idle vibrations	m/s <sup>2</sup>	2,0	1,8

\* to be discontinued



1 m<sup>3</sup> per min = 1000 liters/min = 16,6 l/sec - Operating pressure 5,9÷6,2 bar