(E 😡 🔘 🖻

HAZET Sabre saw

For cutting sheet metal up to 3 mm in thickness and sheet steel up to 4 mm

Ideal for short radius cut

Light and very powerful - With adjustable blade guide

Adjustable air expulsion direction

With 3 bimetal blades with 18, 24 and 32 teeth per inch

Threaded coupling 1/4" Gas for hoses with Ø 10 mm

Stroke 10 mm - Oscillations/min 10000 - Air consumption 1,5 l/min

Idle noise 78,9 db(A) - Idle vibrations 7,7 m/s²

Overall length 215 mm - Weight 450 g

Code E 1135 1000 E 1135/1	Each €	3	1
---------------------------	---------------	---	---

Bi-metal flexible blades for air reciprocating saws

In HSS high speed steel

Suitable for E 1135/1 sabre saw

Overall length 100 mi

Pitch mm / Teeth per inch		1 / 24	0,75 / 32
Code		D 3884 0024	D 3884 0032
D 3884	Per pack €		
For cutting		steel sheet	plastic and wood
3	pack	5	5





"Mouse" type, with handy, synthetic resin body

With integrated muffler 75,1 dB at 6 bar

Working pressure 0,35 ÷ 0,6 MPa (3,5 ÷ 6 bar)

Threaded coupling 1/4" BSP (Gas)

Overall length 130 mm - Weight 110 g

Code E 1138 1100	E 1138/11	Each €	1	1
0000 E 1100 1100	L 1100/11	Laoire		ı



Products tested according to test method of the acoustic level, in accordance with ISO 3744 standard for the safety of acoustic emissions

With milled nut for hose insertion

Threaded coupling 1/4" BSP (Gas) with unified quick coupling

Overall length 100 mm - Weight 0,2 kg

►ABC 70015 - Professional version

L 1130/3 - #/DC=== - FT01essional Version				
	Code E 1138 2000*	E 1138/2	Each €	3 1
	Code E 1138 3000	E 1138/3	Each €	3 1

^{*} not an *ABC TOOLS item

Version with blast nine 300 mm long

version with blast pipe 300 mm long					
	Code E 1138 4000	E 1138/4	Each €	3	1

Version with reinforced synthetic resin body

Particularly suitable for continuous use With stainless steel blast nozzle

Without muffler

Working pressure 0,35 ÷ 0,6 MPa (3,5 ÷ 6 bar)

Threaded coupling 1/4" BSP (Gas)

Overall length 250 mm - Weight 0,1 kg

Code E 1138 2100 E 1138/21 Each €

With integrated muffler 75,1 dB at 6 bar

Working pressure 0,35 ÷ 0,6 MPa (3,5 ÷ 6 bar)

Threaded coupling 1/4" BSP (Gas)

Overall length 240 mm - Weight 0,1 kg

Code E 1138 2200 E 1138/22 Each €

Complete execution of spiral hose in polyurethane - length 4 m equipped with fitting with

Gas $\frac{1}{4}$ " with internal Ø 5 mm and external Ø 8 mm Operating pressure 0,35 ÷ 0,6 MPa (3,5 ÷ 6 bar)

E 1138/25 - With blower E 1138/21

E 1138/26 - With blower E 1138/22 with built-in silencer

Code E 1138 2500	E 1138/25	Each €	3	1
Code E 1138 2600	E 1138/26	Each €	3	1

1 m³ per min = 1000 liters/min = 16,6 l/sec - Operating pressure 5,9÷6,2 bar



473

E 1138/3



1