

Quick-change couplings - female type

In nickel-plated brass

Suitable for several applications, resistant, long-lasting, fast and easy to connect

Body in nickel-plated brass - Tempered and nickel-plated steel locking ring

Compatible with most of the couplings and coupling adapters available on the market

Nominal diameter 7,6 mm (5/16")

Air flow 2000 l/min - Max working pressure 12 bar

With coupling for hoses

For hoses with internal Ø mm	6	8	10
Code	E 1140 6106	E 1140 6108	E 1140 6110
E 1140/61 Each €			



With coupling for spiral hoses

For hoses with internal Ø mm	6	8
Code	E 1140 6406	E 1140 6408
E 1140/64 Each €		
For hoses external Ø mm	8	10



With threaded male fitting

Threaded attachment Gas	1/4"	3/8"	1/2"
Code	E 1140 6614	E 1140 6638	E 1140 6612
E 1140/66 Each €			



With threaded female fitting

Threaded attachment Gas	1/4"	3/8"	1/2"
Code	E 1140 6814	E 1140 6838	E 1140 6812
E 1140/68 Each €			



E 7

Hoses fittings

In nickel-plated brass

With threaded male fitting

Threaded attachment Gas	1/4"	3/8"
Code	E 1140 7114	E 1140 7138
E 1140/71 Each €		
For hoses with internal Ø mm	6	6
For hoses external Ø mm	14	14



E 1140/71

Threaded attachment Gas	1/4"	3/8"
Code	E 1140 7314	E 1140 7338
E 1140/73 Each €		
For hoses with internal Ø mm	8	8
For hoses external Ø mm	17	17

With threaded female fitting

Threaded attachment Gas	1/4"	3/8"
Code	E 1140 7614	E 1140 7638
E 1140/76 Each €		
For hoses with internal Ø mm	6	6
For hoses external Ø mm	14	14



E 1140/76

Threaded attachment Gas	1/4"	3/8"
Code	E 1140 7814	E 1140 7838
E 1140/78 Each €		
For hoses with internal Ø mm	8	8
For hoses external Ø mm	17	17