

JUWEL PLUS Micrometers

With $\frac{1}{100}$ mm (0,01 mm) graduation - Accuracy DIN 863

Hard metal convex tips, carefully lapped and super-finished with perfect parallelisms and planarity - Matt chromed frame and thermoinsulating pads

Tempered steel spindle \varnothing 6,5 mm - Matt chromed bush and drum \varnothing 18 mm

With sensitive clutch, locking lever, micrometer standard (excluded size 25), individual identification number and certificate of conformity

Individually checked and tested - Supplied with case

Type with internal sensitive clutch

Sensitive clutch in advanced position, integrated in the drum for one-hand-use



Measuring range	mm	0÷25*	25÷50	50÷75	75÷100**	200÷225
Code		H 4310 0025	H 4310 0050	H 4310 0075	H 4310 0100	H 4310 0225
H 4310	Each €					

Set of micrometers

Consisting of:

4 micrometers **H 4310** of 25 - 50 - 75 - 100 mm

3 micrometer standard of 25 - 50 - 75 mm

In wooden case

Code H 4310 9000	H 4310/9	Each €	1
-------------------------	-----------------	--------	---



Measuring range	mm	0÷25	25÷50
Code		H 4311 0025	H 4311 0050
H 4311	Each €		



Type with pawl and ratchet clutch

With micrometer standard (excluding size 25)

Measuring range	mm	0÷25	25÷50	50÷75	75÷100	100÷125	125÷150
Code		H 4324 1025	H 4324 1050	H 4324 1075	H 4324 1100	H 4324 1125	H 4324 1150
H 4324/1	Each €						
Measuring range	mm	150÷175	175÷200	200÷225	225÷250	250÷275	275÷300
Code		H 4324 1175	H 4324 1200	H 4324 1225	H 4324 1250	H 4324 1275	H 4324 1300
H 4324/1	Each €						



Universal micrometers

With $\frac{1}{100}$ mm (0,01 mm) graduation - Accuracy DIN 863

Carefully lapped and super-finished tips with perfect parallelisms and planarity

Measuring range 0÷25 mm

Matt chromed drum \varnothing 18 mm

Interchangeable anvils for measuring different profiles with just one micrometer

With individual identification number

Supplied with wooden box

Code H 4325 2000	H 4325/2	Each €	1
-------------------------	-----------------	--------	---



Digital micrometers

With $\frac{1}{100}$ mm (0,01 mm) graduation - Accuracy DIN 863

With contact tips with **hard metal insert**, precision ground and lapped

Painted frame with thermoinsulating pads

Tempered steel spindle \varnothing 6,5 mm - Measuring force 5÷10 N

Functions: ON/OFF, SET for zero-setting the scale, **ABS/INC** for converting between relative and absolute measures **UNIT** for converting mm/inc

Wide, easy to read, **5-digit 11 mm display** - SR-44 battery powered

With sensitive clutch, locking lever and individual identification number

Individually checked and tested - Supplied with case and certificate of conformity

Measuring range	mm	0÷25	25÷50	50÷75	75÷100
Code		H 4326 3025	H 4326 3050	H 4326 3075	H 4326 3100
H 4326/3	Each €				

