

JUWEL PLUS Special dial indicators

1/100 mm (0,01 mm) graduation

Rotating dial to read from above with two pointers and tolerance indices
 Suitable for mounting on control templates - Attachment Ø 8 and 28 mm h6

Measuring range 3 mm - With back feeler and metal case

Dial diameter	mm	40	58
Code		H 4472 1040	H 4472 1058
H 4472/1	Each €		
One turn of the pointer = 10 mm	mm	0,5	1



JUWEL PLUS Dial indicators

With vertical feeler - Shank for attachment Ø 8 mm h6
 With individual identification number - Supplied in case

1/10 mm (0,1 mm) graduation

Measuring range 10 mm

Suitable when the tool is used in an inappropriate way for an indicator and for this reason it is frequently replaced

Dial Ø 58 mm with one pointer

Every turn of the main pointer corresponds to 10 mm

With flat backing plate and metal case

Code H 4472 2000	H 4472/7	Each €	1
------------------	-----------------	--------	---

1/10 mm (0,1 mm)



1/100 mm (0,01 mm) graduation

Accuracy DIN 878

With rotating dial and tolerance indices

Measuring range 0,4 mm

Dial Ø 40 mm with one pointer - **Shockproof**

With double-sided graduated scale 20 - 0 - 20, flat backing plate and metal case

Free stroke for piece positioning 4,5 mm

Code H 4473 1000	H 4473/1	Each €	1
------------------	-----------------	--------	---

Shockproof

Measuring range 0,8 mm

Dial Ø 58 mm with one pointer - **Shockproof**

With double-sided graduated scale 40 - 0 - 40, flat backing plate and metal case

Free stroke for piece positioning 9 mm

Code H 4473 2000	H 4473/2	Each €	1
------------------	-----------------	--------	---

Shockproof

Measuring range 3 mm

Dial Ø 32 mm with two pointers

Flat backing plate and metal case

Every turn of the main pointer corresponds to 0,5 mm

Code H 4476 0000	H 4476/0	Each €	1
------------------	-----------------	--------	---

Dial Ø 40 mm with two pointers

Flat backing plate and synthetic resin case

Every turn of the main pointer corresponds to 0,5 mm

Code H 4476 1000	H 4476/1	Each €	1
------------------	-----------------	--------	---

Dial Ø 40 mm with two pointers - **Shockproof** with protective cap

Removable flat backing plate and metal case

Every turn of the main pointer corresponds to 0,5 mm

Code H 4476 2000	H 4476/2	Each €	1
------------------	-----------------	--------	---

Shockproof

Dial Ø 40 mm with two pointers

Shockproof with protective cap

Protected against dust penetration and effects of temporary immersion in water and oil

Removable flat backing plate and metal case

Every turn of the main pointer corresponds to 0,5 mm

Code H 4476 3000	H 4476/3	Each €	1
------------------	-----------------	--------	---

IP 67

Shockproof and protected against water and oil immersion

Measuring range 5 mm

Dial Ø 40 mm with two pointers

Flat backing plate and synthetic resin case

Every turn of the main pointer corresponds to 0,5 mm

Code H 4477 1000	H 4477/1	Each €	1
------------------	-----------------	--------	---

1/100 mm (0,01 mm)

