

Mitutoyo Precision height gauges with vernier scale

With tempered and ground steel rod and vernier scale

1/50 mm (0,02 mm) reading

Base with ergonomic hand grip

Finely ground and lapped sliding surface

Matt chromed vernier scale with micrometric regulation

Black millimeter graduation rod for easy reading

Scriber with hard metal insert



Matt chromed vernier scale

Measuring and tracing range	mm	200	300
Code		H 4820 0200	H 4820 0300
H 4820	Each €		
Accuracy	± mm	0,03	0,04
Total height with base	mm	341	525
Base dimensions	mm	100x65x35h	135x95x45h



Micrometric regulation



Mitutoyo Digital height gauges

Type with "ABSOLUTE" system to set

to zero only once and to maintain it until the battery is replaced

Strong version, base with ergonomic handle

1/100 mm (0,01 mm) graduation

Wide, easy to read, 10 mm high figures display 10 mm

SR44 battery powered

With handle for moving the slide

Maximum level of measuring precision also at high sliding speed

ORIGIN, ON/OFF, PRESET, ABS,

INC, HOLD functions with possibility of reversing the counting direction

Marking tip with hard metal

tipped point

Prepared for data output "Digimatic" with cable H 4845/6



Handle for moving the slide

Slide locking lever



Display with figures 10x38 mm

Measuring and tracing range	mm	300	600
Code		H 4823 0300	H 4823 0600
H 4823	Each €		
Accuracy	± mm	0,04	0,06
Total height with base	mm	507	812
Base dimensions	mm	160x122x73h	181x142x74h



ABSOLUTE™

Type for two tempered and ground steel columns, that ensure the highest measuring stability

1/100 mm (0,01 mm) graduation - High precision

Protection level IP 40 (against solid bodies > 1 mm)

Base with ergonomic handle - Sliding surface ground and finely lapped

Marking tip with hard metal tipped point

Wide, easy to read, 5-digit 9 mm display

SR44 battery powered

Maximum level of measuring precision also at high sliding speed

ON/OFF, HOLD, PRESET, ZERO/ABS functions, with possibility of reversing the counting direction


Prepared for data output "Digimatic" with cable H 4845/6

Measuring and tracing range	mm	300	600
Code		H 4824 0300	H 4824 0600
H 4824	Each €		
Accuracy	± mm	0,02	0,05
Total height	mm	475	802
Base dimensions	mm	135x91x45h	180x120x54h
Weight	kg	4,7	9,5

Spare tips with hard metal tip

Code H 4824 3000	H 4824/3	Each €	 1
-------------------------	-----------------	--------	---

Cable for data transmission to PC - USB 2.0 outlet - Length 2 m

Code H 4845 6000	H 4845/6	Each €	 1
-------------------------	-----------------	--------	---

