


JUWEL PLUS Control vee blocks

In special tempered steel - Support surfaces and ground V slots, tolerance $\pm 0,02$ mm

Dimensions LxDxh mm	100x45x45	150x55x55	200x70x70
Code	H 4857 0100	H 4857 0150	H 4857 0200
H 4857 Per pair €			
For shafts \varnothing mm	5÷30	5÷42	5÷56



JUWEL PLUS Straight edges

Accuracy DIN 874/00 - Tempered and ground - With lapped edge and thermoinsulating pads
Suitable for checking surface planarity - Supplied with case

H 4862 - In steel - Burnished version

H 4863 - In stainless steel

Length mm	75	100	150	200	300	400	500
Code H 4862 ...	—	0100	0150	0200	0300	0400	—
H 4862 Each €							
Code H 4863 ...	0075	0100	0150	0200	0300	0400	0500
H 4863 - INOX Each €							



H 4862 - Burnished



H 4863 - INOX

Control rulers without graduation

For checking surface planarity - With control surfaces and ground edges

Transversal and rectangular surface - With certificate of control and individual identification number



Accuracy conforming to DIN 874 Grade 0
Normalized steel

Total length mm	500	1000	1500
Code	H 4864 0500	H 4864 1000	H 4864 1500
H 4864 Each €			
Section mm	50x10	60x12	70x15
Planarity $\pm \mu\text{m}$	7	12	17
Weight kg	2	5,7	12,4

Accuracy conforming to DIN 874 Grade I

H 4866 - In normalized steel

H 4867 - In stainless steel

Total length mm	500	750	1000	1500	2000*	3000*
Code	H 4866 0500	H 4866 0750	H 4866 1000	H 4866 1500	H 4866 2000	H 4866 3000
H 4866 Each €						
Code	H 4867 0500	H 4867 0750	H 4867 1000	H 4867 1500	H 4867 2000	H 4867 3000
H 4867 - INOX Each €						
Section mm	40x8	50x10	50x10	60x12	70x14	100x16
Planarity $\pm \mu\text{m}$	12	16,5	21	29	37	54
Weight kg	1,3	3	4	8,4	12	26

* With section I and two slots for manual transport



Accuracy conforming to DIN 874 Level II
In normalized steel

Total length mm	500	750	1000	1500	2000
Code	H 4868 0500	H 4868 0750	H 4868 1000	H 4868 1500	H 4868 2000
H 4868 Each €					
Section mm	30x6	40x8	40x8	50x10	60x12
Planarity $\pm \mu\text{m}$	20,5	27	33	45,5	58
Weight kg	0,7	2	2,5	5,8	11,2

Rulers for assembly operations

In steel profile with lightening holes - Accuracy conforming to DIN 874

Suitable for aligning machineries and plants during construction - Ground surface and side

H 4868/3 - Accuracy level 0 - I section with wide support surface

H 4868/6 - Accuracy level 1 - I section with narrow support surface

Total length mm	1000	1500	2000	3000
Code	H 4868 3100	H 4868 3150	H 4868 3200	H 4868 3300
H 4868/3 Each €				
Code	H 4868 6100	H 4868 6150	H 4868 6200	H 4868 6300
H 4868/6 Each €				
Section h x l (H 4868/3) mm	160x50	160x50	160x50	180x60
Section h x l (H 4868/6) mm	100x30	100x30	120x40	140x40
Weight (H 4868/3) / (H 4868/6) kg	12 / 5	18 / 7,5	24 / 15	45,5 / 26



H 4868/3
Wide support surface



H 4868/6
Narrow support surface

