

BMI Pocket levels




In synthetic resin ABS, with protected vial in unbreakable transparent body
Suitable for masons, carpenters

H 5143 - With one horizontal and one vertical vial - Dimensions 100x35x13 mm

H 5144 - With one horizontal vial and a round one at the edge

Prismatic base suitable for cylindrical pieces - Dimensions 150x25x23 mm

H 5145 - With 3 vials for checking at 0° - 45° - 90°, bevelled angles and magnetic base
Dimensions 200x42x17 mm

Code H 5143 0000	H 5143	Each €		1
Code H 5144 0000	H 5144	Each €		1
Code H 5145 0000	H 5145	Each €		1



H 5143

H 5144 - Prismatic base



H 5145 - Magnetic base

Type for straight edges

With nickel-plated sheet metal spring to be inserted in wooden, plastic, metal straight edges etc.
Spring length 20 mm - Dimensions 150x25x22 mm

Code H 5145 3000	H 5145/3	Each €		1
------------------	-----------------	--------	---	---



With spring to be inserted on straight edges

Type for use with plumb line

Base with groove with 2 loops for passing the plumb line
Suitable also for use on corners and edges
With clip for attaching to the belt - Dimensions 120x29x17 mm

Code H 5145 6000	H 5145/6	Each €		1
------------------	-----------------	--------	---	---



For use with plumb line

ABC TOOLS Water levels

With strong plastic air vent tap
Cylindrical body in unbreakable synthetic resin with millimeter graduation
To be used with H 5146/1 connection hose
Graduation 120 mm
Body diameter 30 mm
Height 255 mm

Code H 5146 0000	H 5146	Per pair €		1
------------------	---------------	------------	---	---

Flexible connecting hose in antifreeze PVC

Transparent, internally and externally smooth
Extremely flexible and strong, resistant to abrasions, it is indicated for non-corrosive liquid transfer
Do not use with hot water and put it under pressure for prolonged time
Working temperature from -15°C to +65°C
Ø internal / external 10 / 14 mm
Roll length 50 m

Code H 5146 1000	H 5146/1	Each €		1
------------------	-----------------	--------	---	---



ABC TOOLS Chalking lines

Magnesium alloy body and 30 m cotton thread

To be used as a chalking line or as a plumb line, by holding the ring and the reel
Fast thread extraction: press the "PUSH" button without turning the crank
Anchoring hook of the thread in tempered steel with specific housing for storing it when it is not used

With tank for chalking powder and stainless steel clip for attaching to the belt

H 5148 - With perfectly straight side walls for a linear stand on the ground

H 5148/2 - With **fast thread rewind system** through crank, **ratio 5:1**

Code H 5148 0000	H 5148	Each €		6
Code H 5148 2000	H 5148/2	Each €		6

Spare thread - Length 30 m

Code H 5148 1000	H 5148/1	Each €		40
------------------	-----------------	--------	---	----



H 5148

H 5148/2
Fast rewind system

Special chalking powder - In vials

H 5149/4 - Red

H 5149/5 - Blue

Content	ml	100	250
Code		H 5149 4100	H 5149 4250
H 5149/4	Each €		
Code		H 5149 5100	H 5149 5250
H 5149/5	Each €		



H 5149/4 ml 100



H 5149/5 ml 250