

Self-levelling laser levels

Self-levelling tools for indoors and outdoors works, they project a horizontal and vertical line that can be activated individually or simultaneously (90° cross line)
Class 2 laser 635 nm frequency

Type with intersecting lines with inclination function

Optical indication of the exit from the levelling area

Self-levelling range 5° - Accuracy 0,5 mm / 1 m

Laser ray range 10 m - With thread 1/4" for use on tripods

Powered by 2 AA, 1,5 V batteries - About 15 h of autonomy

Dimensions LxDxh 55x85x75 mm - Weight 260 g

Code H 5170 6000	H 5170/6	Each €		1
------------------	-----------------	--------	---	---



Support with universal clamp

Suitable for all laser tools with attachment 1/4"

Two lock rings to adjust the height and the position of the tool

Code H 5170 9600	H 5170/96	Each €		1
------------------	------------------	--------	---	---

JUWEL PLUS Square levels

Cast iron body, ground surfaces - Accuracy according to DIN 877 and 2276-1

Thermoinsulated handle against the heat of the hand

Suitable for checking planarity and orthogonality, for shafts alignment

3 prismatic bases and one flat base

2 vials: a longitudinal one, adjustable in 0 position through a screw and a transversal one (small)

With individual identification number

Supplied in wooden case

Side lengths	mm	150	200	250
Code		H 5173 1150	H 5173 1200	—
H 5173/1 - Sensitivity 0,5 mm	Each €			
Code		H 5173 3150	H 5173 3200	—
H 5173/3 - Sensitivity 0,1 mm	Each €			
Code		H 5173 5150	H 5173 5200	H 5173 5250
H 5173/5 - Sensitivity 0,02 mm	Each €			



JUWEL PLUS Linear levels

Cast iron body, ground surfaces - Accuracy according to DIN 877 and 2276-1

With 2 vials: a longitudinal one, adjustable in 0 position through a screw and a transversal one (small)

Prismatic base (lxh 50x45 mm), thermoinsulated handle against the heat of the hand

Suitable for checking planarity and orthogonality, for shafts alignment

With individual identification number - Supplied in wooden case

Length	mm	150	200	300
Code		H 5177 6150	H 5177 6200	H 5177 6300
H 5177/6 - Sensitivity 0,1 mm	Each €			
Code		H 5177 8150	H 5177 8200	H 5177 8300
H 5177/8 - Sensitivity 0,05 mm	Each €			
Code		H 5178 0150	H 5178 0200	H 5178 0300
H 5178 - Sensitivity 0,02 mm	Each €			



JUWEL PLUS Digital square levels

3 tools in 1: goniometer, inclinometer and level for inclination from 0° to 360° (90° x 4)

Aluminium body and precision support base, prismatic

LCD display, 3 figures, with **automatically reversible reading** - Dimensions 150x30x60h mm

Supplied with case, with individual identification number and certificate of conformity

H 5180/1 - HOLD and ZERO functions for incremental zero setting

Resolution 0,1° - Accuracy : at 0° and 90° ± 0,1° - in the remaining range ± 0,2°

3V CR2032 battery powered - Approx. autonomy 2000h

H 5180/2 - Magnetic support base

HOLD, CAL, REF for taking a reference parameter and selecting the measurement unit in mm/m, %, in/ft or degrees (°)

Resolution 0,05° - Accuracy ± 0,15°

With SUOND acoustic signal and LIGHT button to enlighten the display

2 AAA 1,5V batteries powered - Approx. autonomy 2000h

Protection level IP65 (against water and dust penetration)

Code H 5180 1000	H 5180/1	Each €		1
Code H 5180 2000	H 5180/2	Each €		1



H 5180/1



H 5180/2

IP
65

