

Hand tachometer

Pocket type for left and right rotation - **With contact detection**
 4 figures for counting up to 9999 rounds - Max speed 7000 rpm
 With reset knob
 Metal body with 1 steel knob and 1 PVC conical tracer

Code H 5260 1000	H 5260/1	Each €		1
------------------	----------	--------	---	---



ABC TOOLS Speedometers

To read **rpm, without contact**, by using a light beam and a reflecting sticker

Type with digital graduation through 5 figures LCD display
 Powered by 2 AAA, 1,5V batteries with charge status indication
 Working temperature from -10°C to +50°C
 Automatic switch off after 30 secs

Version without memory function

Max measuring distance 450 mm
 Measuring time: 0,5 sec. - Accuracy: 0,02% (1 digit)
 Measuring range for rpm: 1,00÷60000 min⁻¹ (optical measure)
 Supplied in transparent "Quadropack", with 1 set of reflecting strips H 5261/9

Code H 5261 0000	H 5261	Each €		1
------------------	--------	--------	---	---

Version with MEM function that enables to display the last measured value, the max/min and the mean value

Max measuring distance 600 mm
 Measuring time: 0,5 sec. - Accuracy: 0,02% (1 digit)
 Measuring range for rpm: 1,00÷99999 min⁻¹ (optical measure)
 Supplied with case, 1 set of reflecting strips H 5261/9

Code H 5261 1000	H 5261/1	Each €		1
------------------	----------	--------	---	---

Version with remote measurement (through a light beam and a reflecting sticker) **and contact measurement** with a coupled adapter and its accessories (tracers or wheels)
 Suitable to detect the **speed and the length**

With **MEM function** to display the last value, the max/min value and the mean value and **MODE** to select the measuring range (m/min, m/sec, ft/min, ft/sec, in/min, m, ft, in, rpm)
 Measuring range 1,00 ÷ 99999 rpm (optical) / 0,10 ÷ 19999 rpm (contact)
 Peripheral speed (with 6" wheel) 0,10 ÷ 1524 m/min / 0,40 ÷ 5000 ft/min / 4,00 ÷ 60000 in/min
 Length measurement (with 6" wheel) 0,00 ÷ 99999 m / 0,00 ÷ 99999 ft / 0,00 ÷ 99999 in
 Accuracy: 0,02% (either 1 digit or 0,02 m and 1,00 in resolution)
 Supplied with case including:
 1 extension H 5261/5, 1 Ø 48,4 mm wheel H 5261/6, 1 Ø 31,8 mm wheel H 5261/7, 1 conical ferrule H 5261/8, 1 convex ferrule H 5261/82, 1 set of reflecting stickers H 5261/9

Code H 5261 3000	H 5261/3	Each €		1
------------------	----------	--------	---	---



Type with analogue graduation

Plastic body
 With Ø 70 mm dial with scale 10÷100 - Accuracy ±0,5%
 Suitable for fast rpm graduation and for immediately identifying the values oscillations
 Measuring range: 10÷10000 rpm and 1÷1000 m/min (for m/min graduation, refer to the red scale)
 With PEAK/HOLD button to stop the pointer on the last measured value
 Selecting ring with 3 positions to select the right measuring range (1x - 10x - 100x)
 Working temperature from 0°C to +40°C
 Supplied with 0,1 m wheel, 1 conical tracer, 1 convex tracer and 1 extension shaft
 Case dimensions LxDxh 250x205x60 mm


Code H 5261 4000	H 5261/4	Each €		1
------------------	----------	--------	---	---



Accessories for speedometers H 5261/3

- H 5261/5 - Extension
- H 5261/6 - Wheel Ø 48,4 mm (6") - For peripheral speed from 0,10÷1524 m/min
- H 5261/7 - Wheel Ø 31,8 mm (0,1 m) - For peripheral speed from 0,10÷1999 m/min
- H 5261/8 - Conical tracer
- H 5261/82 - Convex tracer
- H 5261/9 - 10 reflective, sticker strips (suitable for all speedometers)

Code H 5261 5000	H 5261/5	Each €		1
Code H 5261 6000	H 5261/6	Each €		1
Code H 5261 7000	H 5261/7	Each €		1
Code H 5261 8000	H 5261/8	Each €		1
Code H 5261 8200	H 5261/82	Each €		1
Code H 5261 9000	H 5261/9	Each €		1



H 5261/5



H 5261/6



H 5261/7



H 5261/9

