

## AMPROBE Thermal hygrometer

For measuring **relative humidity** and **temperature** in assistance services, maintenance and control of clean rooms, air conditioned buildings, warehouses, productive areas, silos, etc. - With integrated probe

**Functions:** HOLD to save values, MIN/MAX values, conversion °C/°F and relative measurement between two measurements

**Measuring ranges:** - relative humidity 5% ÷ 95% - temperature -20°C ÷ +60°C (-4°F ÷ +140°F)

Accuracy : - relative humidity ±3% - temperature ±0,8°C / ±1,6°F

Resolution: - relative humidity ±0,1% - temperature ±0,1°C / °F

Wide LCD display with double indication, 3 1/2 figures, for simultaneous reading of temperature and relative humidity

9V battery powered - About 85h of autonomy - Automatic switch off

Working temperature from 0°C to +60°C with humidity <80% - Supplied with case

Code H 5418 0000	H 5418	Each €		1
------------------	--------	--------	---	---



## JUWEL PLUS Refractometers

**Type for checking and measuring emulsions of coolants and lubricants**

Suitable for workshops, industries

With this tool the fluids can always be used at their optimal concentration

It extends the life of cutting tools and machines preventing rust

Measuring range: - Oechsle method 0÷130° - Division 1°

- Brix method 0÷32% - Division 0,2%

With adjustable eyepiece - Supplied with case

Code H 5420 1000	H 5420/1	Each €		1
------------------	----------	--------	---	---



**Type for checking battery fluid, antifreeze and cleaning liquid**

It indicates the solidification point of the liquid and the electrolyte concentration of the battery

Measuring range: - propylene cooling liquid from -50° C to 0° C

- ethylene cooling liquid from -40°C to 0° C

With adjustable rubber-coated eyepiece - Supplied with case

Code H 5420 2000	H 5420/2	Each €		1
------------------	----------	--------	---	---



## Inspection cameras

Tools suitable for **inspections and visual diagnosis** in hard-to-reach areas such as electrical panels, pipelines, hollows in walls, tool machines, car workshops, auto electricians, installers and maintenance technicians etc.

Suitable for professional documentation through video recording and/or photos

### ABC TOOLS

**With 1 m semi-flexible cable with integrated probe with lens Ø 16 mm and LED light**

LCD 3,5" monitor, wireless function, zoom 3x and resolution 320x240

File format: JPEG (photos), AVI (video) - Output video PAL/NTSC - Image resolution 704x575

Power supply: monitor with Li-ion battery 3,7 V 1,2Ah (autonomy 4 h)

camera with 4 AA 1,5 V batteries

Working temperature -10°C ÷ +50°C

Camera dimensions 195x165x55 mm

Supplied with plastic case with 4 GB Micro SD and battery charger

Code H 5426 1000	H 5426/1	Each €		1
------------------	----------	--------	---	---

**H 5426/6 - Head Ø 9 mm with 1 m cable**

**H 5426/7 - 1 m flexible extension** that can be connected to other extensions up to 9 m

Code H 5426 6000	H 5426/6	Each €		1
------------------	----------	--------	---	---

Code H 5426 7000	H 5426/7	Each €		1
------------------	----------	--------	---	---



IP 67



H 5426/6  
Head Ø 9 mm



H 5426/7  
Extension 1 m

### HAZET

**1 m flexible cable with micro lens Ø 4,9 mm and enhanced LED light**

Simple use with one hand

With switch for turning the framing from 90° to 0°

Wide **3,5" TFT LCD color monitor**, high resolution

Immediate photo and video display - File format: JPEG (photo), MPEG4 (video)

Resolution: images 640x380, video 30 FPS

4 AA, 1,5V batteries powered

Improved probe attachment with optional possibility to use old or additional probes

Camera dimensions 275x123x55 mm

Supplied with plastic case and 4 GB SD card and magnetic hook for hanging

Code H 5427 0000	H 5427	Each €		1
------------------	--------	--------	---	---



Ø 4,9 mm

Switch for turning  
the frame from  
90° to 0°



## Tester for batteries

Tool that indicates the charge status of AA, AAA, C, D, block (9V) and button-type batteries (only small size)

**3 colours scale**, easy to read, indicating the remaining charge

**Measuring range: 1,5 V - 9,0 V**

With sliding support to adapt to battery dimensions - It works without battery

Code H 5428 5000	H 5428/5	Each €		1
------------------	----------	--------	---	---

