# **ABC** Tools Technical sprays

Sprays with "360° valve" have a:

1) special valve for content distribution in all positions

2) distributing straw suitable for accurate product dosage and to spray in hard-to-reach places All sprays DO NOT contain ozone depleting gases - Content 400 ml

#### Sold in indivisible packages 🍞 👘

#### «MARINOIL» - UNLOCKING PROTECTIVE LUBRICANT

- lubricates, protects from corrosion and prevents any electrical and mechanical problems caused by humidity and salt water
- suitable for marine applications, nautical equipment, marine engines, homes etc.
- dissolves rust and fouling, quickly releasing the locked parts, deep-penetrating and protecting
- water-repellent, does not contain acids and doesn't damage metal, paint, etc.

|  | Code K 3832 0000 | K 3832 | Each € | • | 6 |
|--|------------------|--------|--------|---|---|
|--|------------------|--------|--------|---|---|

#### «LUBRIFRESH» - UNIVERSAL CUTTING OIL

ideal lubricant for mechanical work and removing burrs
excellent surface adhesion, even on irregular, convex parts; flows with the right fluidity even on parts in hard-to-reach places where it is not possible to insert a brush or other tool

especially effective on stainless steels and hard and soft metals

| Content  | ml     | 50          | 400         |
|----------|--------|-------------|-------------|
| Code     |        | K 3833 6050 | K 3833 6400 |
| K 3833/6 | Each € |             |             |
| <b>*</b> | pcs.   | 20          | 6           |

#### «CINGHIAFERM» - NON-SLIP PROTECTIVE FOR BELTS

- for flat belts made of rubber, leather, cotton or other fibres
- also suitable for trapezoidal vehicle belts and for all types of transmission belts
- protects against cuts and chaps, resists the accumulation of dirt, therefore keeping

| treated surfaces clean |        |        |            |
|------------------------|--------|--------|------------|
| Code K 3834 0000       | K 3834 | Each € | <b>S</b> 6 |

### «GRAFITENE» - DRY GRAPHITE LUBRICANT

has an uniform, balanced surface expansion

• indispensable for special applications where, due to high temperature (up to 140°C), it is advisable to avoid the use of hydrocarbons suitable for bearings, shafts, sliding guides, gears, springs, and leaves, conveyors, pressure moulding machines

• also used on moving pieces or in mounting and assembly phase

|  | Code K 3835 0000 | K 3835 | Each € | <b>3</b> 6 |
|--|------------------|--------|--------|------------|
|--|------------------|--------|--------|------------|

## «GRASSOSPRAY» - UNIVERSAL ADHESIVE LUBRICATING GREASE

multi-use, water repellent, adhesive grease
ideal for lubricating bearings, metal cables and transmission chains

- long-time protection against wear, corrosion and humidity
- Code K 3836 0000
   K 3836
   Each €
   €
   6

## «PERMANENT PTFE» - UNIVERSAL DRY ADHESIVE LUBRICATING • with PTFE, long-lasting

- multi-use, water-repellent, adhesive, with exceptional lubricating properties for temperatures from -15°C to +250°C
- ideal for lubricating bearings, metal cables and transmission chains
- long-time protection against wear, corrosion and humidity
- Code K 3836 2000
   K 3836/2
   Each €
   ⊕ 6

# «COMPRESSED AIR» - DRY AND CLEAN AIR, COLORLESS, ODORLESS

 the dry and clean air jet allows for the removal of particles deposited in hard-to-reach places of delicate machineries, the removal of particles and contaminating agents from any kind of electronic equipment, such as computers, control devices, etc.

6

www.abctools.it

• with straw for better directing the air flow

• use in vertical position and spray for very short time to avoid the freezing effect

Code K 3838 0000 K 3838 Each €

50 ml

VALVE

VAL VE

360°



Technical sprays

VAL VE

360°

400 ml



VAL VE

360°