Suitable for grease guns K 3895÷K 3898/3 Threaded shank M 10x1 - Without heads - DIN 1283

Safety and flexible type for high performance

K 3899/11 -

In rubber coated metal spiral, - Ø 13,5 mm

Resistant to grease and oil (bursting pressure 1650 bar)

K 3899/13 - ₹ABC>700LS

In reinforced thermoplastic material with polyester braid - Ø 10 mm

Length	cm	30	50	70
Code		K 3899 1130	K 3899 1150	_
K 3899/11	Each €			
Code		K 3899 1330	K 3899 1350	K 3899 1391
K 3899/13	Each €			



Rigid type, in steel

Overall length 130 mm				
Code K 3899 1500	K 3899/15	Each €	3	1



Heads for compressor hoses

Threaded shank M 10x1

Suitable for grease guns with hexagonal head 15 mm (K 3902/4 - K 3902/5)

Code K 3900 1000	K 3900/1	Nickel-plated	Each €	> 10
Code K 3900 2000	K 3900/2	Steel	Each €	> 10





Suitable for grease guns with round head 22 mm

In nickel-plated brass

Code K 3900 2700	K 3900/27	At 90°	Each €	३ 10
Code K 3900 3000	K 3900/3	Straight	Each €	> 10





With concave head for grease guns with pointed head (K 3902/11)

Suitable for injection grease guns K 3890

Code K 3901 1000 K 3901/1 Nickel-plated Each €
--



With conical head for grease guns with concave head (K 3902/12)

Code K 3901 2000	K 3901/2	Brass	Each €	> 10



With simple ring for sealing

For grease guns with semispherical «Hydraulic» head (K 3902/7÷K 3902/9)

Code K 3901 3000 K 3901/3	Steel Each €	> 10
---------------------------	--------------	----------------



With gripping pincers with 4 jaws

Long-lasting, for high pressure

For grease guns with semispherical «Hydraulic» head (K 3902/7÷K 3902/9)

Code K 3901 4000 K 3901/4 Steel Each € 10



Grease guns with screw cover «Stauffer» model

in brass				
Gas threading	inches	1/8	1/4	1/4
Code		K 3902 2001	K 3902 2002	K 3902 2003
K 3902/2	Each €			
Body	Ø mm	17	20	31

