


HUNTSMAN Epoxy adhesives**Bicomponent for universal use - 2011**

Contact adhesive with bicomponent chemical reaction that polymerizes at room temperature
Flexible, strong, good resistance to dynamic loads, high cutting and stripping resistance, suitable for bonding metals, ceramics, glass, rubber, plastics and common material
For handling in 7 hours, it reaches 50% of hardening in 10 hours

In pack of	ml	50	300
Code		K 3935 1050	K 3935 1300
K 3935/1	Each €		
		6 Bi-cartridges	12 Tubes

**Bicomponent for fast universal use - 2012**

Contact adhesive with bicomponent chemical reaction, fast hardening
Transparent, auto-leveling, flexible, strong, good resistance to cutting traction 19 N/mm², high cutting resistance
For handling in 20 minutes, it reaches 50% of hardening in about 2 hours
Pack with 6 double-cartridges of 50 ml

Code K 3935 2000	K 3935/2	Each €	 1
-------------------------	-----------------	--------	--


**Bi-component epoxy thixotropic adhesive for metals - 2013**

Contact adhesive with chemical reaction, versatile, ideal for glueing metals
For a wide array of metals, ceramics, glass, plastic rubber and many other materials
Filler, does not trickle, up to 5 mm in thickness
For handling in 7 hours, it reaches 50% of hardening in 10 hours
Pack with 6 double-cartridges of 50 ml

Code K 3935 4000	K 3935/4	Each €	 1
-------------------------	-----------------	--------	--


**Epoxy thixotropic adhesive (heat resistant), fast action - 2014**

Contact adhesive with bicomponent chemical reaction, highly heat resistant (up to 140°C) and to chemical agents
Filler paste, it does not trickle up to 5 mm in thickness, adhesive on a wide array of substrates, resistant to cutting traction 19 N/mm²
For handling in 20 minutes, it reaches 50% of hardening in 2 hours

In pack of	ml	50	200
Code		K 3935 6050	K 3935 6200
K 3935/6	Each €		
		6 Bi-cartridges	6 Bi-cartridges

**Epoxy thixotropic adhesive (heat resistant), slow action - 2015**

Contact adhesive with bicomponent chemical reaction, very resistant
Highly reinforced thixotropic paste, it does not trickle up to 10 mm in thickness, for composite material, high cutting and stripping resistance, resistant to cutting traction 18 N/mm²
For handling in 4 hours, it reaches 50% of hardening in 10 hours


In pack of	ml	50	200
Code		K 3935 7050	K 3935 7200
K 3935/7	Each €		
		6 Bi-cartridges	6 Bi-cartridges



K 8

HUNTSMAN Accessories for epoxy adhesives**Mixer Turbo**

Laminated type with internal spiral, for mixing grade better than common helical nozzle
Mixing nozzle for double-cartridges - In synthetic resin

For cartridges from	ml	50	200
Code		K 3935 8050	K 3935 8200
K 3935/8	Each €		
Total length	mm	105	190
	pcs.	10	50

**Manual applicator guns in synthetic resin - For double cartridges of 50 ml**

The use combined with the mixer K 3935/8 of 50 ml enables, in a single operation, to obtain the exact mix and dose of the two double-cartridges components
With adapter for double-cartridges with non-homogeneous mixing ratio (for ex. K 3935/6 of 50 ml)
Overall length 200 mm - Weight 180 g

Code K 3935 9100	K 3935/91	Each €	 1
-------------------------	------------------	--------	--

