

Self-locking rope clamps

In forged steel with burnished and tempered turnbuckle - For copper wires and steel ropes

For ropes Ø	mm	3÷8	5÷10	8÷16
Code		L 2214 0038	L 2214 0510	L 2214 0816
L 2214	Each €			
For copper wires	mm ²	6÷35	16÷70	50÷150
Capacity	kg	1000	1700	3000
Breaking load	kg	1700	3000	5500
Weight	kg	0,85	1,1	1,8




Beta split pins

L 2217/1 - In galvanized steel

L 2217/3 - In stainless steel AISI 304 - INOX

Ø round bar	mm	2	3	3,5	4	5	6
Code	L 2217 ...	1002	1003	1035	1004	1005	1006
L 2217/1	Each €						
Code	L 2217 ...	3002	3003	—	3004	3005	3006
L 2217/3	Each €						



L 2217/3 - INOX

Linchpins

In galvanized steel

Ø round bar	mm	4,5	6	8	10
Code		L 2217 5045	L 2217 5006	L 2217 5008	L 2217 5010
L 2217/5	Each €				



Turnbuckles

Type with two eyelets

L 2222 - In pressed steel - Galvanized - With CE marking

L 2222/2 - In stainless steel AISI 316 - INOX

Threading	M	5	6	8	10	12	14	16	20	22	24
Code		L 2222 0005	L 2222 0006	L 2222 0008	L 2222 0010	L 2222 0012	L 2222 0014	L 2222 0016	L 2222 0020	L 2222 0022	L 2222 0024
L 2222	Each €										
Code		L 2222 2005	L 2222 2006	L 2222 2008	L 2222 2010	L 2222 2012	—	—	—	—	—
L 2222/2 - INOX	Each €										
Body length	mm	70	90	110*	125*	140*	170	190	220	240	260
Capacity L 2222	kg	100	150	300	470	650	800	1250	1800	2250	2800
Capacity L 2222/2	kg	35	70	135	175	275	—	—	—	—	—

* Body length L 2222/2 M 8 = 120 mm - M 10 = 150 mm - M 12 = 200 mm




Type with eyelet and hook

L 2223 - In pressed steel - Galvanized - With CE marking

L 2223/2 - In stainless steel AISI 316 - INOX


Threading	M	5	6	8	10	12	14	16	20	22	24
Code		L 2223 0005	L 2223 0006	L 2223 0008	L 2223 0010	L 2223 0012	L 2223 0014	L 2223 0016	L 2223 0020	L 2223 0022	L 2223 0024
L 2223	Each €										
Code		L 2223 2005	L 2223 2006	L 2223 2008	L 2223 2010	L 2223 2012	—	—	—	—	—
L 2223/2 - INOX	Each €										
Body length	mm	70	90	110	120*	140*	170	190	220	240	260
Capacity L 2223	kg	25	45	75	115	150	210	340	650	900	1200
Capacity L 2223/2	kg	20	35	50	85	110	—	—	—	—	—

* Body length L 2223/2 M 10 = 150 mm - M 12 = 200 mm



Type with 2 hooks in pressed steel - Galvanized finishing - With CE marking

Threading	M	5	6	8	10	12	14	16	20	22	24
Code		L 2223 5005	L 2223 5006	L 2223 5008	L 2223 5010	L 2223 5012	L 2223 5014	L 2223 5016	L 2223 5020	L 2223 5022	L 2223 5024
L 2223/5	Each €										
Body length	mm	70	90	110	125	140	170	190	220	240	260
Capacity	kg	25	45	75	115	150	210	340	650	900	1200



Type with 2 brackets in pressed steel - Galvanized finishing - With CE marking

Threading	M	10	12	14	16	20	22	24
Code		L 2224 1010	L 2224 1012	L 2224 1014	L 2224 1016	L 2224 1020	L 2224 1022	L 2224 1024
L 2224/1	Each €							
Body length	mm	125	140	170	190	220	240	260
Capacity	kg	450	650	750	1000	1400	1800	2000

