

## Hose clips – non perforated band

Conforming to DIN 3017

With **non-perforated band** and **rounded edges** to ensure a tight seal **without damaging** the hose

High-resistance and reusable several times

High clamping with low tightening torque

Particularly suitable for reparations and assembly operations, in industry, in automotive, on hard and soft surfaces

**Sold exclusively in indivisible pack**  (see note below the table)

Band width 12 mm - Hex head 7 mm



**L 6570/2 - Entirely in galvanized steel** - Mod. NP12 - W1 - Clamping force 4,5 Nm

**L 6572/2 - Band and guard in stainless steel AISI 430** - Mod. NPS12 - W2

Screw in galvanized steel - Clamping force 5 Nm

**L 6574/2 - Entirely in stainless steel AISI 304** - Mod. NPSS12 - W4

Suitable for **corrosive and moist environments** (shipyards, food industry, etc.) - Clamping force 5 Nm

**L 6576/2 - Entirely in stainless steel AISI 316L** - Mod. NPSS12M - W5

Suitable for **maritime sector, petrochemical and food industry** - Clamping force 5 Nm

For hoses with	Ø mm	16±27	20±32	23±35	25±40	30±45	32±50	40±60	50±70	60±80	70±90	80±100	90±110
<b>Code</b>	<b>L 6570 ....</b>	<b>2016</b>	<b>2020</b>	<b>2023</b>	<b>2025</b>	<b>2030</b>	<b>2032</b>	<b>2040</b>	<b>2050</b>	<b>2060</b>	<b>2070</b>	<b>2080</b>	<b>2090</b>
<b>L 6570/2</b>	Each €												
<b>Code</b>	<b>L 6572 ....</b>	<b>2016</b>	<b>2020</b>	<b>2023</b>	<b>2025</b>	<b>2030</b>	<b>2032</b>	<b>2040</b>	<b>2050</b>	<b>2060</b>	<b>2070</b>	<b>2080</b>	<b>2090</b>
<b>L 6572/2</b>	Each €												
<b>Code</b>	<b>L 6574 ....</b>	<b>2016</b>	<b>2020</b>	<b>2023</b>	<b>2025</b>	<b>2030</b>	<b>2032</b>	<b>2040</b>	<b>2050</b>	<b>2060</b>	<b>2070</b>	<b>2080</b>	<b>2090</b>
<b>L 6574/2</b>	Each €												
<b>Code</b>	<b>L 6576 ....</b>	<b>2016</b>	<b>2020</b>	<b>2023</b>	<b>2025</b>	<b>2030</b>	<b>2032</b>	<b>2040</b>	<b>2050</b>	<b>2060</b>	<b>2070</b>	<b>2080</b>	<b>2090</b>
<b>L 6576/2•</b>	Each €												
For hoses with	Ø mm	100±120	110±130	120±140	130±150	140±160	150±170	160±180	170±190	180±200	190±210	200±220	
<b>Code</b>	<b>L 6570 ....</b>	<b>2100</b>	<b>2110</b>	<b>2120</b>	<b>2130</b>	<b>2140</b>	<b>2150</b>	<b>2160</b>	<b>2170</b>	<b>2180</b>	<b>2190</b>	<b>2200</b>	
<b>L 6570/2</b>	Each €												
<b>Code</b>	<b>L 6572 ....</b>	<b>2100</b>	<b>2110</b>	<b>2120</b>	<b>2130</b>	<b>2140</b>	<b>2150</b>	<b>2160</b>	<b>2170</b>	<b>2180</b>	<b>2190</b>	<b>2200</b>	
<b>L 6572/2</b>	Each €												
<b>Code</b>	<b>L 6574 ....</b>	<b>2100</b>	<b>2110</b>	<b>2120</b>	<b>2130</b>	<b>2140</b>	<b>2150</b>	<b>2160</b>	<b>2170</b>	<b>2180</b>	<b>2190</b>	<b>2200</b>	
<b>L 6574/2</b>	Each €												
<b>Code</b>	<b>L 6576 ....</b>	<b>2100</b>	<b>2110</b>	<b>2120</b>	<b>2130</b>	<b>2140</b>	<b>2150</b>	<b>2160</b>	<b>2170</b>	<b>2180</b>	<b>—</b>	<b>—</b>	
<b>L 6576/2•</b>	Each €												

 25 pcs. from Ø 16-27 to Ø 32-50 - 10 pcs. from Ø 40-60 / • L 6576/2: 25 pcs. up to Ø 40-60 - 10 pcs. from Ø 50-70



**L 6635 - Entirely in galvanized steel**

For hoses with Ø	mm	12±20	16±25	20±32	25±40	32±50	40±60	50±70	60±80	70±90	80±100	90±110
<b>Code</b>	<b>L 6635 ....</b>	<b>0012</b>	<b>0016</b>	<b>0020</b>	<b>0025</b>	<b>0032</b>	<b>0040</b>	<b>0050</b>	<b>0060</b>	<b>0070</b>	<b>0080</b>	<b>0090</b>
<b>L 6635*</b>	Each €											

\* To be discontinued

**L 6639 - Entirely in stainless steel AISI 304**

Suitable for **corrosive and moist environments** (shipyards, food industry etc.)

For hoses with Ø	mm	12±20	16±25	20±32	25±40	35±50	40±60	70±90	90±110	110±130	120±140	130±150
<b>Code</b>	<b>L 6639 ....</b>	<b>0012</b>	<b>0016</b>	<b>0020</b>	<b>0025</b>	<b>0035</b>	<b>0040</b>	<b>0070</b>	<b>0090</b>	<b>0110</b>	<b>0120</b>	<b>0130</b>
<b>L 6639*</b>	Each €											

 100 pcs. up to Ø 50±70 - 50 pcs. from Ø 70±90 to Ø 130±150

\* To be discontinued



Cardboard box 10 pcs.

**Sold exclusively in indivisible pack**

**L 6571 - Entirely in galvanized steel** - Mod. NP12 - W1 - Clamping force 4,5 Nm

**L 6573 - Band and guard in stainless steel AISI 430** - Mod. NPS - W2

Screw in galvanized steel - Clamping force

**L 6575 - Entirely in stainless steel AISI 304** - Mod. NPSS - W4

Suitable for **corrosive and moist environments** (shipyards, food industry, etc.)

Clamping force 5 Nm

For hoses with Ø mm	Code L 6571 ....	L 6571 Each €	Code L 6573 ....	L 6573 Each €	Code L 6575 ....	L 6575 Each €	Larghezza nastro mm
8÷12	1008		1008		1008		9
10÷16	1010		1010		1010		9
12÷22	1012		1012		1012		9
16±27	1016		1016		1016		9
25±40	1025		1025		1025		9
30±45	1030		1030		1030		9
32±50	2032		2032		2032		12
40±60	2040		2040		2040		12

Band width 12 mm



L 6570/2 - W1



L 6572/2 - W2



L 6574/2 - W4  
INOX AISI 304

L 6576/2 - W5  
INOX AISI 316L



L 6635



L 6639



L 6571 - W1

L 6573 - W2

L 6575 - W4 INOX AISI 304