Shoes with the following minimum requirements: safety toe cap able to withstand up to 200J, suede or imitation leather upper and minimum upper height, as well as the following basic additional requirements: anti-perforation midsole (P)

Safety Cat. S1-P

Made entirely of suede leather - Ankle boot model

With padding to protect the malleolusa

Anti-perforation midsole - Removable anatomical inner sole, anti-bacteria and anti-fungal

litryl rubber sole, oil resistant and anti-static						
Size	42	44	45			
Code	M 1986 1042	M 1986 1044	M 1986 1045			
M 1986/1* Per pair €						

^{*} To be discontinued



Safety Cat. S1-P

In suede leather, with cordura inserts and breathable liner

Extra large steel toe cap - Steel anti-perforation midsole

Dual density polyurethane toe cap that is oil resistant and anti-static, with non-skid ridges

Removable anatomical inner sole, anti-bacteria and

anti-fungal

M 1990/1 - Low version

M 1990/2 - Ankle boot version

W 1990/2 - Alikie boot version								
Size		40	41	42	43	44	45	46
Code	М 1990	1040	1041	1042	1043	1044	1045	1046
M 1990/1	Per pair €							
Code	М 1990	2040	2041	2042	2043	2044	2045	2046
M 1990/2	Per pair €							



Safety Cat. S3

All grain leather

Absorbent, breathable inner liner

Sole in oil resistant, anti-static nitryl rubber, with anti-perforation midsole

Removable anti-bacteria, anti-fungal, anatomical inner sole

Size	40	41	44	45
Code	M 1994 5040	M 1994 5041	M 1994 5044	M 1994 5045
M 1994/5** Per pair	€			

^{*} To be discontinued



















Energy-absorbing heel

Safety Cat. S5 - With steel anti-perforation midsole

Particularly suitable for use on construction sites, warehouses, stores, mechanical industry, transport, maintenance, etc.

Made entirely of soft nitryl rubber, resistant to low temperatures

Steel safety toe cap - With inside lining

Nitryl rubber sole, oil and heat resistant and anti-static, with non-skid ridges

Size		40	41	42	43	44	45
Code	M 2002	2040	2041	2042	2043	2044	2045
M 2002/2	Per pair €						





Safety shoe covers - EN 20345

Shoe covers for visitors, suitable for providing protection against crushing and knocking hazards during industrial site visits

With extra-light aluminium-titanium toe, resistant up to 200 J Non-slip sole with high grip coefficient, resistant to hydrocarbons Light, ergonomic, suitable for any type of shoe with or without heel Size 39-43, adjustable using a buckle with Velcro

Provided in a comfortable shoe-holder bag





