## STAINLESS STEEL

Type for typographers with knurled tips - Polished finish

Tweezers

With rear spike

Overall length 150 mm **B** 1601 Code B 1601 0000



Type with straight rounded knurled tips - Polished finish

Gr. 130 and 150 with guide pin

Overall length	mm	130	150	160	250	300
Code		B 1603 0130	B 1603 0150	B 1603 0160	B 1603 0250	B 1603 0300
B 1603	Each €					
<b>3</b>	pcs.	10	10	10	10	10

Each €

**>** 10





# Electronics cutters - "Super-Knips®"

In stainless steel - Polished version - 3 - DIN ISO 9654

Hardened cutting edges with hardness HRc 54

Handles coated with soft thermoplastic resin - With spring MM

Shape suitable for prolonged use without making the hand tired

Overall length 125 mm - Weight 35 g

#### Straight, without wire catcher - Flush cut

It cuts low-resistance Ø 1,6 mm - medium-resistance Ø 1,0 mm wires

B 1798/8 - "Standard" version - Very thick, red/blue two component handles

B 1/98/81 - "ESD" \	ersion/	<ul> <li>Dissipative - Very thick, black</li> </ul>	/gray two component handles
Lunghezza totale	mm	125	140
Code		B 1798 8000	B 1798 8140
B 1798/8	Each €		
Code		B 1798 8100	_
B 1798/81	Each €		
Cuts low resistence wire Ø	mm	1,6	2,1
Cuts medium resistence wi	reØ mm	1,0	1,2







Forma 1

#### Straight, without wire catcher with max Ø 0,8 mm - Flush cut

It cuts low-resistance Ø 1,6 mm - medium-resistance Ø 1,0 mm wires

With wire catcher

B 1798/9 - "Standard" version - Very thick, red/blue two component handles

B 1798/91 - "ESD" version - Dissipative - Very thick, black/gray two component handles

Code B 1798 9000	B 1798/9	Each <b>€</b>	<b>3</b>	6
Code B 1798 9100	B 1798/91	Each <b>€</b>	3	6





### Bent at 60°, without wire catcher - Flush cut

For cutting operations with the use of tips only also in hard-to-reach places It cuts low-resistance wires  $\varnothing$  1,0 mm - medium-resistance wires  $\varnothing$  0,6 mm

<b>«Standard» version</b> - Very thick, red/blue two-component handles						
	Code B 1798 1000	B 1798/10	Each €	<b>6</b>		





Co

# **Cable shears**

## With stainless steel cutting edges - INOX

Two-component handles - With spring MM and closing lever For electrical cables (aluminium and copper) with 24 mm² section

Opening for cables max Ø 10 mm

Ove

verall length 160 mm			
ode B 2144 0160	B 2144	Each €	<b>3</b>





#### With stainless steel blade Folding, with blade liner lock

Ergonomic and comfortable rubber grip

Length: open 200 mm - closed 120 mm - Blade length 70 mm

Provided with nylon sheath with belt loop

Code B 2173 1000 B 2173/1 Each € **>** 12

